Home Audio

Amplifiers . . . . . .49~50
Audio-Technica 57, 58
AudioSource . . .45, 48, 49
Breathe Audio 50
CD Players 62, 63
Ceiling Speakers . .44~46, 50~52
D/A Convertor 57
DVD Players 62, 63
Equalizers 64
Indoor/Outdoor Speakers 50, 58, 59
Infrared Repeaters . . .53, 55, 56
In-Wall Speakers 45~46, 52
Jobsite . . . . . .51~53
MCM Custom Audio 44~48, 56~60
MG Electronics 59
Phono Preamplifiers . . .57
Receivers . . . . . .62~64
Sherwood 63
Sony 61, 62
Speaker Brackets/Stands 58, 59
Speakers (freestanding) . . . . .58~60
Speaker Distribution . .47, 48, 51, 54
SpeakerCraft . . . . .54~56
Speco Technologies 46, 59
Subwoofers 45, 50
Turntables 58
Video Projectors 61
Volume Controls 46~48, 54

MCM CUSTOM AUDIO Single Point Stereo Ceiling Speaker

- ✔8" poly cone woofer
- ✔Left and right channel from one speaker
- ✔2-way design
- ✔Round ceiling mount

Single ceiling speaker allows connection of both left and right channels, while maintaining separation throughout the rest of the audio system. It is perfect in larger areas were separate left/right speaker systems are impractical or undesired. Rotating quick tabs easily attach to existing ceiling or wallboard, without the need for additional hardware. **Features:** •8" polypropylene cone, dual voice coil woofer •Rubber surround •Dual ½" mylar dome tweeters •White textured ABS frame **Specifications:** •Power capacity: 30W/60W RMS/peak, each channel •Frequency response: 55Hz~20KHz •Impedance: 8ohm per channel •SPL: 89dB (W/M) **Dimensions:** •Outer frame diameter: 10¾" •Required cutout: 9⅜" diameter •**Sold individually**

Order #	MSRP	(1–3)	(4–11)	(12–up)
51-882	$79.95	$45.95	$41.95	$39.95

MCM CUSTOM AUDIO Single Point Stereo Ceiling Speaker



- ✔6½" poly cone woofer
- ✔Left and right channel from one speaker
- ✔2-way design
- ✔Round ceiling mount

Identical to item #51-882 in a more compact size. White perforated steel grill and ABS frame match virtually any decor. Attached mounting tabs allow fast easy mounting in existing wallboard. Easy connection is made via two sets of color coded push terminals, which accepts up to 14AWG wire. **Specifications:** •Power capacity: 25W/60W RMS/peak per channel •Frequency response: 70Hz~20KHz •Impedance: 8ohm per channel •Sensitivity: 88dB •Overall frame diameter: 9" •Required cutout: •7½" •Mounting depth: 3¼" •**Sold individually**

Order #	MSRP	(1–3)	(4–11)	(12–up)
51-881	$54.95	$31.95	$29.95	$28.95

MCM CUSTOM AUDIO Compact Eyeball Ceiling Speaker Pair

- ✔Fully pivotal frame
- ✔Attractive curved grill
- ✔Ultra compact design

CLEARANCE

Compact high performing ceiling speaker may be adjusted from 0~30° in any direction, while still appearing flat in the ceiling. **Features:** •3½" treated paper cone woofer •Rubber surround •½" mylar dome tweeter, mounted at the base of the woofer cone for perfect phase alignment •White textured ABS frame •Perforated white steel grill **Specifications:** •Power capacity: 30W/60W RMS/peak •Frequency response: 80Hz~20KHz •Impedance: 8ohm •SPL: 89dB (W/M) **Dimensions:** •Outer frame diameter: 6½" •Required cutout: 5⅝" diameter •Mounting depth: 2¾" •**Sold in pairs**

Order #	MSRP	(prs.)
50-8790	$99.95	$33.00

MCM CUSTOM AUDIO Ceiling Mount Speaker Pair with Pivotal Tweeter

- ✔2-way design
- ✔1" pivotal dome tweeter
- ✔Round ceiling mount

Ideal as main speakers, surround sound or remote speaker applications. Also an excellent choice for background music, paging and general audio applications. Pivotal tweeter allows high frequencies to be focused in the direction of the listening area, instead of directly at the floor. White plastic frame and painted steel grill compliments any decor. Attached mounting brackets easily mount in ceiling or wall board without the need for additional hardware. 8ohm. **Sold in pairs.**

Order #	Speaker Size	Power Capacity RMS/Peak	Frequency Response	SPL	Overall Frame Diameter	Cutout Hole	Mounting Depth	MSRP	(1-3)
50-6245	5¼"	25W/60W	80Hz~20KHz	89dB	8"	6½"	2½"	$74.95	$42.95
50-6246	6½"	25W/60W	70Hz~20KHz	90dB	9"	7½"	2⅝"	79.95	47.95
50-6247	8"	30W/80W	80Hz~20KHz	90dB	10¾"	9⅜"	3⅜"	99.95	58.95

MCM AUDIO SELECT™ Ceiling Mount Speaker Pair

- ✔Efficient dual cone design
- ✔Round ceiling mount

Low cost dual cone speaker pair is ideal for background music, paging and general audio applications. White plastic frame and painted steel grill compliments any decor. Attached mounting brackets easily mount in ceiling or wall board without the need for additional hardware. 8ohm. **Sold in pairs.**

Order #	Speaker Size	Power Capacity RMS/Peak	Frequency Response	SPL	Overall Frame Diameter	Cutout Hole	Mounting Depth	MSRP	(1-3)
50-6240	5¼"	15W/30W	110Hz~20KHz	90dB	8"	6½"	2½"	$44.95	$24.95
50-6241	6½"	15W/30W	100Hz~18KHz	90dB	9"	7½"	2⅝"	59.95	39.95
50-6242	8"	20W/40W	80Hz~20KHz	91dB	10¾"	9⅜"	3⅜"	74.95	43.95

MCM CUSTOM AUDIO 8" Three-Way In-Wall Speaker Pair

- ✔3-way design
- ✔1" pivotal dome tweeter
- ✔Rectangular wall mount

This speaker pair combines all of the critical and most-asked-for features, for an outstanding price. **Features include:** •Polypropylene cone 8" woofer with rubber surround and 1.38" voice coil •2" mylar dome midrange •1" dome pivotal tweeter with diffraction lens •Independent -0, -3, and -6dB adjustments for mid and high frequencies •12dB/octave crossover. Color coded push terminals accept up to 12AWG wire **Specifications:** •Power capacity: 75W/150W RMS/peak •Frequency response: 34Hz~23KHz •Impedance: 8ohm •Sensitivity: 90dB •Overall frame dimensions: 14¼ x 10" •Required cutout: •12¾" x 8½" •Mounting depth: 3½" •**Sold in pairs**

Order #	MSRP	(1–3)	(4–11)	(12–up)
50-6374	$249.00	$149.00	$135.00	$125.00



MCM AUDIO SELECT™ In-Wall Speaker Pairs

- ✔2-way design
- ✔1" soft dome tweeter
- ✔Rectangular wall mount

Ideal as main speakers, surround sound or remote speaker applications. Two-way design includes a 6dB crossover, polymica cone woofer and 1" soft dome tweeter, for high frequency response up to 20KHz. Attached mounting brackets easily mount to wall board without the need for additional hardware. 8ohm. Compatible with 2 x 4 stud walls. **Sold in pairs.**

Order #	Woofer Size	Power Capacity RMS/Peak	Frequency Response	Overall Frame Dimensions	Cutout Hole	Mounting Depth	MSRP	(1-3)
50-6370	5¼"	25W/60W	60Hz~20KHz	11" x 7⅝"	6½" x 9⅝"	2¼"	$74.95	$44.95
50-6371	6½"	30W/60W	50Hz~20KHz	12" x 8¾"	7⅞" x 10¾"	3¼"	109.00	63.95

MCM 1-800-543-4330 Fax 1-800-765-6960

MCM CUSTOM AUDIO Compact In-Wall Speaker System

NEW



- ✔Mounts in a double gang box
- ✔Aluminum cone
- ✔Rubber surround

Rugged 2½" driver is mounted in an attractive square faceplate that is the same size as a double gang wall switch or AC outlet. When used alone, it is perfect for moderate volume music and voice reproduction in public areas, on kiosks or retail displays. Used in pairs, and combined with a subwoofer, it is perfect for any high fidelity audio application including home theater and whole-house audio. **Specifications:** •Power capacity: 20W/30W RMS/peak •Frequency response: 100Hz~20KHz •Sensitivity: 85dB (W/M) •Nominal impedance: 8ohm •Front panel dimensions: 4⅝" (H) x 5" (W) •Mounting depth: 1¾" **•Sold individually**

Order #	MSRP	(1-3)	(4-up)
50-7908	$59.95	$34.95	$32.50





MCM CUSTOM AUDIO Micro In-Wall Speaker System

- ✔Mounts in a single gang box
- ✔Includes high pass capacitor

A rugged 2" full range driver is mounted in an attractive rectangular faceplate that is the same size as a standard wall switch or AC outlet. When used alone, it is perfect for voice reproduction in public areas, on kiosks or retail displays. Used in pairs, and combined with a subwoofer, it is perfect for any high fidelity audio application including home theater and whole-house audio. **Specifications:** •Power capacity: 10W/20W RMS/peak •Frequency response: 300Hz~20KHz •Sensitivity: 85dB (W/M) •Nominal impedance: 8ohm •Front panel dimensions: 4⅝" (H) x 3" (W) •Mounting depth: 1¾" **•Sold individually**

Order #	MSRP	(1-3)	(4-up)
50-7907	$39.95	$26.95	$25.95

MCM CUSTOM AUDIO Compact Ceiling Speaker System

NEW

- ✔Mounts in standard round ceiling box
- ✔Aluminum cone
- ✔Rubber surroud

Rugged 2½" driver is mounted in an attractive round faceplate that is compatible with commonly available ceiling fan electrical boxes, such as the B618R series from Carlon (MCM #28-17060). Use in this manner allows inconspicuous mounting in a variety of areas where appearance is critical, or electrical codes are an issue. When used alone, it is perfect for moderate volume music and voice reproduction in public areas. Used in pairs, and combined with a subwoofer, it is perfect for any high fidelity audio application including home theater and whole-house audio. **Specifications:** •Power capacity: 20W/30W RMS/peak •Frequency response: 100Hz~20KHz •Sensitivity: 85dB (W/M) •Nominal impedance: 8ohm •Front panel diameter: 5⅜" •Mounting depth: 1¾" **•Sold individually**

Order #	MSRP	(1-3)	(4-up)
50-9045	$59.95	$34.95	$32.50



Speakers mounted at AC receptacle or wall switch height, will virtually disappear into the room.

MG 8" In–Wall Subwoofer

The perfect addition to in–wall, ceiling and small satellite speaker systems, this is a perfect match any installed speaker system of 6½" or less. **Features:** •Dual voice coil 8" long throw woofer •30 oz. magnet •Ribbed treated paper cone •Foam surround •Ported front baffle •Dual channel 12dB/octve low pass crossover •Feed through connections satellite speakers (full range) •White steel grill and PVC frame **Specifications:** •Power capacity: 125W/250W max (both channels combined) •Frequency response: 40Hz~500Hz (with included crossover) •Crossover slope: 12dB/octave •Impedance: 8ohm per channel •Dimensions (overall): 10" (W) x 14⅛" (H) •Required cutout: 8¾" (W) x 12¾" (H) •Mounting depth 3¾" **•Sold individually**

Order #	(1–3)	(4–up)
50-6369	$59.95	$54.95

AUDIOPLEX TECHNOLOGY 8" In–Wall Subwoofer

The perfect addition to in–wall and small satellite speaker systems. The dual voice coil 8" long throw woofer features a 13.3 oz. magnet, ultra–rigid injection molded polypropylene cone, and rubber surround, for outstanding low frequency response down to 38Hz. Included crossover allows simplified connection of satellite speakers, with a high pass frequency of 300Hz. White steel grill and PVC frame blend seamlessly into most walls, and may be painted to match any decor. **Specifications:** •Power capacity: 250W max (both channels combined) •Frequency response: 38Hz~300Hz (with included crossover) •Crossover slope: 12dB/octave at 120Hz •Impedance: 8ohm per channel •Dimensions (overall): 10½" (W) x 14⅛" (H) •Required cutout: 8¾" (W) x 12¾" (H) **•Sold individually**

Order #	(1–3)	(4–up)
51-782	$126.00	$119.00

AudioSource® 8" In-Wall Subwoofer



The perfect addition to in-wall and small satellite speaker systems, this is a perfect match for the MCM #50-7907 micro in-wall speaker. The large poly cone woofer with butyl rubber surround provides low end frequency response essential for augmenting small in-wall and ceiling speakers. White steel grill and PVC frame blend seamlessly into most walls, and may be painted to match any decor. **Specifications:** •Recommended amplifier power: 25W~100W RMS •Frequency response: 40Hz~200Hz •Impedance: 8ohm •Required cutout: 8¾" (W) x 8¾" (H) •Mounting depth: 4" •Mfr. #AS8SW **•Sold individually**

Order #	(ea.)
51-783	$79.95

Pre–Construction Speaker Bracket Pairs

Rugged ABS and perforated sheet metal bracket assemblies greatly ease installation of in–wall and ceiling speakers in new construction applications. Simply attach to wall studs or ceiling joists, prior to drywall installation, for easy location and secure mounting of speaker systems during final installation. ⅜" lip provides perfect finished edge for drywall thickness. Removable mesh plates allow screw or nail mounting to virtually any stud or joist spacing, up to 40" apart. Rectangular in–wall models may be horizontally or vertically mounted (width listed below assumes vertical mount). **All models are sold in pairs. Compatibility: •#50-6681A:** All MCM Custom Audio and most other brand in–wall models **•#50-6686A, 50-6687A:** All MCM Custom Audio ceiling models, with enclosed back–box **•#50-6248, 50-6249:** All MCM Custom Audio and most other brand open back ceiling models

Order #	Type	Speaker Size	Speaker Opening	Min. Stud Width	(1-3 prs.)	(4 prs.-up)
50-6681A	In-wall	6½"	10¾" x 7⅜"	13½"	$19.95	$18.50
50-6686A	Ceiling	6½"	8"	13½"	19.95	17.96
50-6687A	Ceiling	8"	9⅝"	15½"	21.95	19.13
50-6248	Ceiling	6½"	7 1⁄16"	13½"	19.95	17.96
50-6249	Ceiling	8"	9 1⁄16"	15½"	21.95	19.13



MIDLITE® QUALITY CUSTOM PRODUCTS Versa-Tape Pre-Construction Wire Placement



This perforated tape is ideal for holding low voltage cable in place prior to drywall installation. It is useful when the exact location of wall plates is subject to change, or when the cable is installed for long term use, without immediate installation of a wall plate. It can also be considered a low cost alternative to pre-construction brackets. 200' roll.

Order #	(1-3)	(4-up)
50-8915	$34.95	$29.95

MCM CUSTOM AUDIO Stereo Volume Controls



- ✔Standard and impedance matching models
- ✔Conventional rotary design
- ✔Includes white and ivory cover plates

In-wall volume controls utilize high quality multitap audio transformers and smooth 12 position rotary switches to provide full range level control. They are designed for use in distributed audio systems, primarily those involving in-wall and ceiling speaker systems. Available in single gang steel plate and decora style all units are shipped as white, with ivory plates and knobs included for easy color conversion. Standard units are available in 25W RMS and 100W RMS versions, impedance matching models are 100W RMS. Impedance matching design allows of up to 16 pairs of 8ohm speakers to be connected to a single stereo amplifier, and appear as a 4ohm load. **Features:** •Detachable terminal strips accept up to 14AWG wire •Included matching cover plates with decora models •May be mounted in a single gang box or low voltage bracket **Specifications:** •Frequency response: 35Hz~20KHz •Attenuation: -34~0dB, in 12 steps •Impedance matching (applicable models only): x2, x4 and x8ohm

Order #	Style	Impedance Matching	Power Capacity (RMS)	MSRP	(1-3)
50-7850	Decora	No	25W	$39.00	$21.95
50-7860	Plate	No	25W	39.00	21.95
50-7890	Decora	No	100W	45.00	24.95
50-7880	Decora	Yes	100W	49.00	32.95
50-7870	Plate	Yes	100W	49.00	32.95

MCM CUSTOM AUDIO Slide Style Stereo Volume Control

- ✔Impedance matching design
- ✔Attractive slide style
- ✔Compatible with decora plates

Impedance matching design allows use in systems from one to 16 pairs of speakers on a single stereo amplifier. **Features:** •Attractive decora styling with included cover plate •Detachable terminal strips accept up to 14AWG wire **Specifications:** •Power capacity: 100W/180W RMS/max •Frequency response: 35Hz~20KHz •Attenuation: -34~0dB, in 12 steps •Impedance matching: x1, x2, x4 and x 8ohm •Size: Standard single gang •Color: White

Order #	MSRP	(1-3)	(4-11)	(12-up)
50-6377A	$53.25	$31.95	$29.95	$26.95



speco technologies Stereo–to–Mono Mixer

This transformer accepts a signal, from both the left and right amplifier channels, and provides a combined mono output to drive one speaker. Because the inputs are fully isolated, stereo separation is not compromised over the rest of the system. Includes adhesive backed mounting bracket. Power capacity is 30W RMS, both channels combined.

Order #	(1–3)	(4–up)
50-6690	$13.80	$12.45

MCM CUSTOM AUDIO Enclosed 6½" Single Point Stereo Ceiling Speaker

- ✔Dual mylar dome tweeters
- ✔Left and right channel from one speaker
- ✔Round ceiling mount

Unique speaker provides both left and right channels from a single point, while maintaining complete channel isolation. **Features:** •Dual ½" mylar dome tweeters •Dual voice coil polypropylene woofer, with rubber surround •White perforated steel grill and ABS frame •Attached mounting tabs for easy mounting in existing wallboard •Two pairs of red/black color coded push terminals to accept up to 14AWG speaker wire **Specifications:** •Power capacity: 25W/60W RMS/peak per channel •Frequency response: 74Hz~20KHz •Impedance: 8ohm per channel •Sensitivity: 89dB •Overall frame diameter: 9½" •Required cutout: 8" •Mounting depth: 5½" •**Sold individually**

Order #	MSRP	(1-3)	(4-11)	(12-up)
50-9050	$79.95	$47.95	$45.95	$43.95



MCM CUSTOM AUDIO Enclosed 6½" Ceiling Speaker Pair

- ✔6½" woofer
- ✔Pivotal dome tweeter
- ✔Round ceiling mount

Ideal as main speakers in a home theater system, or locate throughout the entire structure in whole-house applications. Designed for good music reproduction, these are also ideal in voice and paging applications. Fully enclosed rear enclosure protects speaker from insulation and other debris when mounted in attic cavity. **Features:** •Poly treated cone woofer with treated foam surround •Pivotal 1" dome tweeter •White perforated steel grill and ABS frame •Attached mounting tabs for easy mounting in existing wallboard •Red/black color coded push terminals to accept up to 14AWG speaker wire **Specifications:** •Power capacity: 25W/60W RMS/peak •Frequency response: 74Hz~20KHz •Impedance: 8ohm •Sensitivity: 91dB •Overall frame diameter: 9½" •Required cutout: 8" •Mounting depth: 5½" •**Sold in pairs**

Order #	MSRP	(1-3)	(4-11)	(12-up)
50-9060	$125.00	$73.95	$70.95	$66.95



MCM CUSTOM AUDIO Enclosed 8" Ceiling Speaker Pair

- ✔8" woofer
- ✔Pivotal dome tweeter
- ✔Round ceiling mount

Features: •Poly treated cone woofer with treated foam surround •Pivotal 1" dome tweeter •White perforated steel grill and ABS frame •Attached mounting tabs for easy mounting in existing wallboard •Red/black color coded push terminals to accept up to 14AWG speaker wire **Specifications:** •Power capacity: 30W/80W RMS/peak •Frequency response: 70Hz~20KHz •Impedance: 8ohm •Sensitivity: 91dB •Overall frame diameter: 11" •Required cutout: 9⅜" •Mounting depth: 7" •**Sold in pairs**

Order #	MSRP	(1-3)	(4-11)	(12-up)
50-9061	$145.00	$84.95	$80.95	$76.95

speco technologies MA Series Ceiling Speaker

Completely enclosed ceiling speaker is the ideal all–purpose solution, covering a wide variety of distributed commercial and residential sound applications. Internal 25V/70V transformer taps are easily selected via the front baffle, allowing final volume balancing to be done after installation. 8ohm position is provided for residential applications. Rear back box provides protection to the speaker plus consistent sound, regardless of location. Polypropylene cone woofers and ported enclosures provide extended frequency response typical of much higher cost units. **Features:** •Rubber surround woofers •1" mylar dome tweeter •Fire retardant ABS rear enclosure •White ABS frame with rotating mounting clips •Easily installs to existing wallboard •Transformer taps: 0.25W, 0.5W, 1W, 2.5W, 5W, 7.5W, 15W, 30W, 40W (#50-7536 only) •**Sold individually**

Order #	Woofer Size	Power Capacity RMS/Peak	Frequency Response	SPL (W/M)	Overall Frame Diameter	Cutout Hole	(1–3)	(4–11)	(12–up)
50-7535	5¼"	30W/60W	57Hz~20KHz	87dB	9.9"	8.2"	$48.95	$42.95	$39.95
50-7536	6½"	40W/80W	34Hz~20KHz	88dB	11.42"	9.74"	58.95	49.95	46.95

speco technologies Enclosed Two–Way In–Wall Speaker Pairs

Easy to install in–wall speakers are ideal for background music, paging, home theater or any general music application. Their wide frequency response and above average power capacity make them ideal as main, surround or background speakers. System consists of a woven fiberglass, blue cone woofer, with rubber surround, and a 1" titanium swivel dome tweeter. The addition of a molded PVC back–box ensures uniform sound quality regardless of mounting location, while protecting the speaker from insulation debris and temperature extremes. Rotating mounting clips allow fast installation in to drywall with no additional hardware. All will mount in a standard 2 x 4 studded wall. Each speaker is 8ohm. **Sold in pairs.**

Order #	Woofer Size	Power Capacity RMS/Peak	Frequency Response	SPL (W/M)	Overall Frame Dimensions	Price Per Pair (1–3)	(4–11)	(12–up)
50-6547	5¼"	40W/80W	55Hz~20KHz	88dB	11.75" (H) x 8.3" (W) x 3.6" (D)	$96.50	$87.00	$77.00
50-6548	6½"	60W/100W	50Hz~20KHz	88dB	12.0" (H) x 8.6" (W) x 4.25" (D)	123.00	111.00	99.95
50-6549	8"	80W/120W	50Hz~20KHz	88dB	14.0" (H) x 10.0" (W) x 4.1" (D)	148.00	133.00	118.00

MCM 1-800-543-4330 Fax 1-800-765-6960

MCM CUSTOM AUDIO
Speaker Selector/ Distribution Panel

Impedance matching speaker selector/distribution network is ideal in situations where up to ten pairs of speakers are to be connected to a single amplifier, and individual on/off selection is required. Additionally, a two–position source selector allows global selection from two different source systems. High–powered non–inductive resistors ensure that the speaker load never falls below 4ohm, even when all ten pairs of speakers are operating. Heavy–duty rocker switches are rugged enough for commercial use, while remaining suitable for residential applications. Detachable terminal strips accept up to 14AWG wire. The rugged steel panel is intended for 19" rack mounting, and occupies two rack spaces. Power capacity: 200W per channel. Overall dimensions: 3.5" (H) x 19" (W) x 2" (D).

Order #	MSRP	(1–3)	(4–up)
50-7655	$199.00	$156.00	$142.00

MCM CUSTOM AUDIO
Four Pair Speaker Selector Switch

Allows simultaneous operation of up to four pairs of 8ohm or 16ohm speakers. Automatic load protection ensures that the amplifier sees a 4ohm or higher load, regardless of speakers selected. The built-in protection circuit inserts resistance only when more than two pairs of speakers are selected. This ensures that maximum power is delivered to the speakers. Additional resistance is inserted only when needed. Amplifier A/B switch allows selection from two different sources allowing greater flexibility. Left and right channels are fully isolated from each other, allowing compatibility with any type of amplifier. Thermo-Tek™ circuit protects switch and components in the event of an overload situation. Power capacity 40W/120W RMS/program. Rear mounted terminal strip accepts up to 10AWG wire. Dimensions: 17" (W) x 2" (H) x 5" (D). Black color.

Order #	MSRP	(1-3)	(4-9)	(10-up)
50-2075	$199.00	$110.25	$99.45	$89.71

Ten Position Speaker Switch

Intended for PA or other monaural applications, this switch box provides individual on/off control of up to ten speaker systems. Power capacity is 100W RMS, internal progressive resistor network keeps amplifier load to a minimum of 2ohm, when ten 8ohm systems are selected. Rear speaker in/out connections are color coded push connectors. Metal case has non-skid rubber feet and stays securely in place. Dimensions: 8" (W) x 2¼" (H) x 4¼" (D). Black color. **Note:** Because low resistance loads can be damaging to some amplifiers, the customer must ensure that the total speaker load will be within the limits of the equipment in use.

Order #	(1-5)	(6-9)	(10-up)
50-6205	$18.95	$18.03	$14.68



Five-Way Speaker Switch Box with Headphone Jack

Tabletop control box allows selection of up to five speaker pairs. Internal 100ohm resistors ensure that amplifier always sees a load, even with all switches off. Progressive switched resistor network ensures that a minimum of 8ohm load is seen by the amplifier (when 8ohm speakers are used), regardless of speakers selected. Front panel ¼" headphone jack allows monitoring of the source. 200W maximum power capacity. All connections are push type. Metal case has non-skid rubber feet and stays securely in place. Dimensions: 8⅛" (W) x 2¼" (H) x 3⅜" (D). Sloped front, black color.

Order #	(1-5)	(6-9)	(10-up)
50-6200	$24.95	$22.95	$20.95

sima
Speaker Selector Switches with Volume Control

Versatile selectors allow connection of up to six pairs of speakers, to two different stereo sources, with individual volume control of each pair. Volume adjustment and impedance matching is accomplished through internal heavy-duty multi-trapped transformers. For each speaker, this allows complete, independent control of each pair, with maximum efficiency, and virtually no generation of heat. Removeable screw terminal strips allow easy connection of multiple cables. **Power capacity:** 18W/50W RMS/program per speaker, 100W/150W RMS/program total. Dimensions: 3" (H) x 17" (W) x 7" (D), including knobs.

Order #	Speaker Pairs	(1–3)	(4–up)
50-6675	Four	$209.00	$194.00
50-6676	Six	251.00	242.00

PG Phoenix Gold
Impedance Protected Speaker Selectors

Low–profile speaker distribution systems enable on/off control to four, six or eight pairs of speakers, while providing impedance protection to the amplifier. Source A/B selector for each zone allows independent selection from two different sources to each speaker pair. Non–inductive resistor network maintains impedance above 4ohm, regardless of the number of 8ohm speakers selected. Since resistors are used instead of commonly used transformers, much wider frequency response is maintained through the selector. Terminal strips accept up to 12AWG wire, and are fully removable to ease installation. **Specifications:** •Power capacity: 70W with impedance protection, 140W without •Aluminum chassis with extruded aluminum front panel •Black color

Order #	Pairs	Dimensions	(ea.)
50-7600	Two	1.75" (H) x 8.5" (W) x 4.5" (D)	$84.95
50-7605	Four	1.75" (H) x 17" (W) x 4.5" (D)	109.00
50-7610	Eight	1.75" (H) x 17" (W) x 4.5" (D)	131.00

ACOUSTIC RESEARCH NEW
Electronic In-Wall Volume Control

Sleek decora style control features electronic up/down adjustment of in-wall or ceiling speaker pairs, with an attractive blue LED digital display. Level may be controlled directly at the switch, or remotely via the included IR remote. The control handles 100W RMS, per channel, and provides impedance matching settings of x1, x2, x4 and x8. This allows up to 16 pairs of 8ohm speakers to be connected to a single amplifier, and appear as a 4ohm load. Compatible with standard decora devices, a single gang cover plate is included.•Mfr. #ARDVC1 **Note:** This unit requires 12VDC, 40mA power source. See www.mcmelectronics.com for power connection details.

Order #	(1-3)	(4-up)
50-8277	$105.00	$99.70



MCM CUSTOM AUDIO
Audiophile Grade Stereo Volume Control

Transformerless volume controls are ideal for use with any in-wall or ceiling speaker system, where local control is desired, and pure sound quality is a must. High–quality, close tolerance audiophile grade resistors are used instead of conventional audio transformers, allowing full 20Hz~20KHz frequency response to pass through to the speaker. This single difference provides performance that is superior to virtually any transformer based control, at any price. Rotary control provides 0~36dB attenuation in 11 steps, with position 12 being off. All models include white and ivory cover plate and knob to match any décor. Detachable terminal strips greatly ease installation and will accept up to 14AWG cable. Control mounts in standard single gang boxes or mud rings, and includes decora style cover plate. Power capacity: 60W RMS per channel.

Order #	MSRP	(1–3)	(4–9)	(10–up)
50-7905	$54.95	$31.95	$29.95	$26.95

Seven Pairs with Two Source Switcher

•Speaker selector with independently rocker type switch for seven pairs of speakers •Two source switches can play either source 1 or source 2 •Built-in impedance protection •Removable connects accept up to 14 gauge wire •Decora style triple gang plate •Separate left and right ground paths for compatibility with all amps, even bridged •Power handling: 50W/CH. (RMS) 100W/CH. (program) •Dimensions: 6.33" (W) x 4.56" (H) x 2.44" (D) •White

Order #	(1-9)	(10-up)
50-2765	$86.95	$83.95

MCM CUSTOM AUDIO
High Power 12 Pair Speaker Switch

Controls up to 12 pairs of speakers with 250W/750W RMS/music power cpacity. High power transformers with selectable taps allow you to obtain maximum power transfer while maintaining a safe load of 4ohm of higher. Because the system is capable of transforming a ⅛ohm load to appear as a 4ohm load, several speaker pairs may be used on a single switch position, allowing more than 12 pairs of speakers to be connected. The left and right channels are completely isolated, allowing compatiblity with any amplifier. Connections are made via rear mounted terminal strip which accepts up to 10AWG wire. Self powered unit needs no AC supply. Dimensions: 17" (W) x 3½" (H) x 6" (D). Black color.

Order #	MSRP	(1-3)	(4-up)
50-6440	$499.00	$389.00	$340.00



MCM CUSTOM AUDIO
High Power Eight Pair Speaker Switch

Controls up to eight pairs of speakers with 250W/750W RMS/music power capacity. High power transformers with selectable taps allow you to obtain maximum power transfer while maintaining a safe load of 4ohm or higher. Because the system is capable of transforming a ⅛ohm load to appear as a 4ohm load, several speaker pairs may be used on a single switch position. The left and right channels are completely isolated, allowing compatibility with any amplifier. Rear mounted terminal strip which accepts up to 10AWG wire. Dimensions: 17" (W) x 3½" (H) x 6" (D).

Order #	MSRP	(1-3)	(4-up)
50-5705	$399.00	$251.00	$240.00



MCM CUSTOM AUDIO
Multi Room Speaker Distribution Strip

Essential for distributed residential sound installations, this terminal strip provides a convenient method of connecting numerous pairs of speakers to a single pair of binding posts. Input terminals are heavy-duty, gold plated brass, five-way binding posts, which will accept single or paired banana plugs or bare wire up to 8AWG. Each output connection features detachable screw terminal strips which accept up to 14AWG wire. Internal PC board circuit is reinforced with internal point–to–point 14AWG wiring, for improved current capacity. Compact size allows easy location behind equipment. Screw holes allow easy wall mounting and rubber feet are included for shelf top use. **Note:** Terminal strip is straight parallel connection and provides no impedance protection. It is intended for use with 70V distributed speakers, or 8ohm systems that utilize impedance matching volume controls. **Specifications:** •Power capacity: 200W RMS per channel •Dimensions: 2" (H) x 2.25" (W) x 10.5" (L), including binding posts.

Order #	MSRP	(1–3)	(4–up)
50-2204	$59.95	$35.95	$32.95

MCM CUSTOM AUDIO
Multi Room Speaker Distribution Strip

Designed for use in multi room sound distribution installations where individual speaker selection is not required. Impedance protection circuit allows up to eight sets of 8ohm speakers to be connected to a stereo amplifier, and appear as a 4ohm load. Completely independent left and right circuits allow compatibility with all amplifier types. Attached mounting plate allows installation into standard 19" racks, or between studs spaced on 16" centers. **Features:** •Color coded push terminals accept up to 8AWG wire •Switchable impedance protection •Non-inductive resistors for full frequency response •Rugged aluminum housing with black finish **Specifications:** •Power capacity: 120W program per channel •Frequency response: 20Hz~20KHz •Dimensions: 3.5" (H) x 19.0" (W) x 2.25" (D)

Order #	MSRP	(1-3)	(4-11)
50-2202	$139.95	$89.95	$84.95

Table-Top Speaker Volume Control

Table-top control center provides external volume adjustment for a single pair of speakers. 12 position rotary control utilizes multi tapped transformers for efficient power transfer, with no heat build-up. Front panel ¼" headphone jack mutes speakers for private listening and is controlled by the volume control. Rear speaker in/out connections are heavy-duty push terminal strips and accept up to 14AWG wire. Heavy metal case has non-skid rubber feet and stays securely in place. Power capacity: 100W RMS per channel. Dimensions: 1¾" (H) x 7" (W) x 3⅝" (D). Silver color.

Order #	(1-4)	(5-9)	(10-up)
50-6216	$34.95	$32.95	$29.95



Two-Way Speaker Switch Box

Tabletop control box allows selection of A/B speaker pairs. Internal 220ohm resistors ensure that amplifier always sees a load, even with both switches off. With both speaker switches in "on" position, speaker pairs are connected in series, allowing use of 4ohm or 8ohm speaker systems, without damage to amplifier. 200W maximum power capacity. All connections are push type. Metal case has non-skid rubber feet and stays securely in place. Dimensions: 6.9" (W) x 2.2" (H) x 3.9" (D). Sloped front, black color.

Order #	(1-5)	(6-9)	(10-up)
50-6185	$18.95	$17.95	$14.29

Speaker Selector Volume Control

These control boxes can operate multiple speaker pairs of 4, 8 and 16ohm impedance in any combination and can be used with either one or two stereo amplifiers. This makes it convenient to listen to different program material in different rooms. 216W Optimatch™ attenuators are employed so that worst case operating conditions will appear as a 4ohm load to the amp. Made in USA.

Order #	Speaker Pairs	(1-3)	(4-9)	(10-up)
50-2390	Six	$399.00	-	-
50-2395	Four	235.00	$231.00	$226.00

NEW

AudioSource®
AMP102 Stereo Power Amplifier

Perfect for high fidelity situations needing an independent audio amplifier. Use as part of a multi-amp configuration in home theater systems, a zone amplifier in distributed sound applications, or as a monitor amp in the studio. This solid no-nonsense amplifier provides 50W RMS per channel, at 8ohm, with less than 0.04% THD, and may be bridged for 150W RMS mono. **Features:** •A/B speaker outputs •12V remote trigger in/out •Two sets of line level inputs with automatic source selection •Source sensing auto power-on •Dimensions: 3.8" (H) x 16.5" (W) x 8.25" (D)

Order #	(ea.)
50-9100	$199.00



NEW

AudioSource®
Stereo Subwoofer Power Amplifier

This independent subwoofer amplifier is ideal in home theater and distributed audio systems where in-wall or other passive subwoofer systems are used. Internally bridged mono amplifier provides output of 300W RMS with less than 0.1% THD. **Features:** •Variable 40Hz~500Hz crossover •Variable 5Hz~50Hz subsonic filter •Two auto sensing line level inputs, each may be configured to accept speaker level signal •LFE input for direct feed from Dolby Digital® receivers •Switchable limiter •Source sensing auto power-on •12V trigger in/out •Dimensions: 3.8" (H) x 16.5" (W) x 13.75" (D)

Order #	(ea.)
50-9140	$369.00

AudioSource®
AMP100 Stereo Power Amplifier

Perfect for high fidelity situations needing an independent audio amplifier. Use as part of a multi–amp configuration in home theater systems, a zone amplifier in distributed sound applications, or as a monitor amp in the studio. This solid no–nonsense amplifier provides 50W RMS per channel, at 8ohm, with less than 0.04% THD, and may be bridged for 100W RMS mono. Additional features include A/B speaker outputs, with front panel control, individual L/R level controls, and heavy duty five–way binding post outputs. Dimensions: 2.75" (H) x 16.5" (W) x 8" (D).

Order #	(ea.)
50-6062	$158.00

SpeakerCraft®
Automatic A/B Line Level Switch

Automatically selects between two line level sources to a single input. Default input-A is selected when no signal is present. When a signal is sensed at input-B, the selector automatically switches to that input. A separate 12VDC, 100mA signal is also provided to trigger other external devices. Trigger sensitivity is fully adjustable from 10~100mV. Off delay (from B back to A after absence of signal) is adjustable in eight steps from 0.5 seconds to 10 minutes. The unit requires 12VDC, AC adaptor is included.

Order #	(1-3)	(4-11)	(12-up)
50-8385	$95.95	$90.95	$80.95

MCM
1-800-543-4330
Fax 1-800-765-6960

AudioSource®
AMP110 Stereo Power Amplifier

NEW

Designed for a wide variety of amplification needs, from powering a pair of speakers from a single source, to delivering very high-quality audio to multiple zones in a distributed system. **Features:** •Front panel controls for level, balance and A/B speaker selection •Two sets of inputs, with auto-switching between each •Pass through output on input #2 •Manual or auto-sensing power control •12V trigger input allows power-on command from external components •12V trigger output allows amplifier to trigger external components •Stereo and bridged mono operation •Heavy-duty binding post speaker outputs •Discrete triple-darlington output components •THD of less than 0.1% (at 8ohm)

Order	Model	Output (4ohm)	Dimensions	(ea.)
50-9110	AMP110	110W RMS x 2CH	3.8" (H) x 16.5" (W) x 13.75" (D)	$249.00

AudioSource®
AMP210/310 Stereo Power Amplifiers

NEW

Designed from the ground-up with the sound contractor in mind, these amplifiers provide performance expected in high quality distributed home audio systems. **Features:** •Front panel controls for level, balance and A/B speaker selection •Two sets of input pairs, each accept line or speaker level signal •Auto-switching between inputs, with adjustable delay •Line level pass through output on input #2 •Rear mounted master level controls (allows gain limiting) •Manual or auto-sensing power control •12V trigger input allows power-on command from external components •12V trigger output allows amplifier to trigger external components •Stereo and bridged mono operation •Heavy-duty binding post speaker outputs •Discrete triple-darlington output components •THD of less than 0.1% (at 8ohm)

Order	Model	Output (4ohm)	Dimensions	(ea.)
50-9120	AMP210	125W RMS x 2CH	3.8" (H) x 16.5" (W) x 13.75" (D)	$349.00
50-9130	AMP310	235W RMS x 2CH	5.5" (H) x 16.5" (W) x 13.75" (D)	459.00

AudioSource®
Amp Five Series Monoblock Amplifiers

Multichannel power amplifiers have become the foundation upon which the best home sound systems are built. With the proliferation of multizone sound reinforcement and state of the art digital surround sound, the amplification of several channels has evolved from a luxury into a necessity. The AudioSource Amp Five Series are fully featured, high current monoblock power amplifiers. High quality, fan cooled discreet output devices stay cool under the most demanding situations. Large toroidal power supplies and oversized capacitors work together to ensure an abundance of headroom while staying stable into loads as low as two ohms. The Amp Five Series is completely modular within its optional rack mountable chassis. This chassis accommodates six 100W, or three 250W modules, other combinations may be utilized. Optional blank face plates are available for a clean front panel. **Other features:** •2ohm stability •Front panel status LEDs •Gain control •Heavy–duty, gold–plated five–way binding posts •Switchable 100Hz, 12dB "low cut" filter •0/180° phase switch •Balanced XLR input •Unbalanced RCA line input •Loop–through line out

#50-6400

#50-6402

#50-6410

Specifications: •THD <0.1% •Frequency response: 20Hz~20KHz •S/N ratio: 95dB •Input sensitivity: 1.0V •XLR input impedance: 20Kohm •Line input impedance: 10Kohm •Damping factor: 200 •Dimensions: 5.5" (H) x see chart (W) x 11.75" (D)

Order #	Model #	RMS Output @4ohm	Width	(ea.)
50-6400	AMP5.1	100W	2.75"	$159.00
50-6402	AMP5.3	250W	5.5"	229.00

Amp Five Series Accessories

Order #	Description	(ea.)
50-6410	Rack mount chassis, 16.5" internal width	$63.95
50-6411	2.75" blank faceplate	13.19
50-6412	4.125" blank faceplate	13.19
50-6413	5.5" blank faceplate	13.19

SpeakerCraft® Automatic A/B Speaker Level Switch

This switching device automatically selects between two stereo amplifiers to a single pair of speakers. It is perfect in situations where installed speakers are used with both a local stereo or home theater system, and a distributed audio system. Default input-A is selected when no signal is present. When a signal is sensed at input-B, the selector automatically switches to that input. A separate 12VDC, 100mA signal is also provided to trigger other external devices. Trigger sensitivity is fully adjustable from 30~300mV. Off delay (from B back to A after absence of signal) is adjustable in eight steps from 0.5 seconds to 10 minutes. Relay contacts are 4PDT, with isolated L/R ground paths. Music power capacity is 100W. The unit requires 12VDC, AC adaptor is included.

Order #	(1-3)	(4-11)	(12-up)
50-8390	$90.00	$85.50	$76.50

Front

Back

Sherwood® Distributed Audio Stereo Receiver

This receiver is perfect for music listening in any room of the home, with conventional left/right stereo output. What sets this apart is four amplifier output channels, creating a self contained, four-zone distributed audio receiver. Up to four pairs of bookshelf, in-wall, in-ceiling or outdoor speakers may be driven directly from this unit, with independent selection of any or all pairs. It is perfect in small residential or commercial background music applications. **Features:** •AM/FM tuner with 30 station presets •Five audio inputs (including tuner) •Phono input •IR remote control •Volume, bass and treble controls •Headphone jack •Power output: 70W RMS x 4 (8ohm), 100W RMS x 4 (4ohm) •THD: <0.2%, 20Hz~20KHz into 8ohm •Dimensions: 5" (H) x 17⅜" (W) x 13" (D) •Mfr. #RX-5502

Order #	(ea.)
50-4640	$209.00

NetMedia Ultra Compact 40W Stereo Amplifier

NEW

Weighing in at less than 6 oz., this miniature stereo amplifier is smaller than a deck of cards, yet delivers an incredible 20W RMS per channel. It is perfect for driving a pair of speakers directly from a portable MP3 player or PC, flat panel TV or any other line or headphone level source. 92% efficient digital amplifier circuit is housed in a rugged extruded aluminum enclosure and is convection cooled, ensuring whisper quiet operation. **Features:** •3.5mm input •Included 3.5mm male/male cable •Detachable Phoenix style speaker connections •LED power indicator •Includes AC adaptor **Specifications:** •Output: 20W x 2CH @ 8ohm •THD 0.11% at 50% rated power •S/N ratio: >99dB •Requires 24VDC, 2A •Dimensions: 1.0" (H) x 2.2" (W) x 2.78" (D).

Order #	(ea.)
50-4600	$99.95

MCM CUSTOM AUDIO Single Channel Amplifier Module

NEW

Compact amplifier is perfect for any general purpose application where a speaker needs to be driven from a line level signal. Its compact size allows it to be mounted most any place, and may be directly attached to the rear of a speaker enclosure. It is ideal for a wide variety of hobby, service and prototype applications. **Features:** •RCA female input •Accepts line level or headphone level signal •12" attached speaker leads •Barrel type power connector **Specifications:** •Input: Line level (80mV) •Output: 12W @ 4ohm •Requires 6~16VDC, 800mA •Dimensions: 1⅝" (H) x 2⅝" (W) x 2" (D)

Order #	MSRP	(1-4)	(5-9)	(10-up)
50-4605	$29.95	$14.95	$13.75	$12.75

breatheaudio™ Elevate™ Whole Home Music System

This complete four zone sound system brings multi–zone, multi–source audio to a new price level. **Features:** •Four independent stereo amplifier channels, one for each zone •Individual keypad control for each zone •Independent selection from two input sources from each zone •Complete control of input source, volume level and system power on/off from each keypad •Infrared repeating from each keypad to control source devices as well as the Elevate™ unit **Elevate™ amplifier includes:** •Elevate base unit •Allport™ connection cable •Two IR emitters •IR remote control •Complete four-room kit also includes four remote keypads **Specifications:** •Power output: 15W RMS x 8 CH •THD: 0.4% •Frequency response: 30Hz~20KHz •Power requirements: 110/220VAC, 50/60Hz, 166W •Dimensions: 3.5" (H) x 8.5" (W) x 12.75" (D)

Order #	Model #	Description	(ea.)
50-4650	BA-2430S	Complete four room kit	$489.00
50-4655	BA-2430DA	Elevate amplifier only	299.00

breatheaudio™ NEW Elevate™ 6.6 Whole Home Music System

This complete six zone, six source sound system brings multi-zone, multi-source audio to a new price level. Purchase the BA-6640MS as the main unit, to drive up to six zones. Add the BA-6640XS Expander to the main unit, to control up to a total of 12 zones. **Features:** •Six independent stereo amplifier channels, one for each zone •Individual keypad control for each zone •Independent selection from up to six input sources from each zone •Complete control of input source, volume level and system power on/off from each keypad •Infrared repeating from each keypad to control source devices as well as the Elevate™ unit. **Complete six zone kit includes:** •Elevate 6.6 base unit •Allport™ connection cable •IR emitters •IR remote control •Six remote keypads **Specifications:** •Power output: 20W RMS x 12 CH •THD: 0.4% •Frequency response: 30Hz~20KHz •Power requirements: 110/220VAC, 50/60Hz, 166W •Dimensions: 3.5" (H) x 17" (W) x 12.75" (D)

Order #	Model #	Description	(ea.)
50-4645	BA-6640MS	Complete Six Zone Kit	$977.47
50-4655	BA-6640XS	Six Zone Expander	299.00

breatheaudio™ Elevate™ Music System Learning Remote Control

Learning IR remote control operates all functions of the Elevate™ Music System, and may be programmed to operate source devices. This allows operation of tuners, satellite receivers, CD or DVD players from any Elevate™ zone, simply by pointing the remote at the wall mounted keypads.

Order #	Model #	(ea.)
50-4651	BA-LRC1	$34.95

breatheaudio™ Pulse™ High Power Stereo Amplifier

Designed for use with the Breathe Elevate™ Music System, this amplifier connects to the Zone1 output, providing additional power. It is perfect for providing party level SPL in large rooms, outdoors or to multiple speaker pairs. 2ohm amplifier stability allows this unit to directly drive four pairs of 8ohm speakers without impedance concerns. **Features:** •3.5mm stereo line level input connection •3~30VAC/DC trigger input **Specifications:** •Power output: 70W RMS x 2 CH @ 8ohm, 100W x 2CH @ 4ohm •THD: 0.08% •Frequency response: 20Hz~20KHz •Power requirements: 110/220VAC, 50/60Hz, 405W (max) •Dimensions: 3.75" (H) x 8.5" (W) x 13.5" (D) •Model #BA-200

Order #	(ea.)
50-4660	$249.00

breatheaudio™ Elevate™ Music System Keypads

Single and two–pack of keypads are available when the Elevate™ amplifier is purchased alone. This allows greater flexibility in allowing the keypads to be installed during construction, and the amplifier to be added later. Each keypad includes black, almond, ivory and white faceplates.

Order #	Model #	Description	(ea.)
50-4656	BA-2430IK	Two pack	$119.00
50-4657	BA-2430KP	Single	59.95

breatheaudio™ Resonate™ 6½" Single Stereo Ceiling Speaker

This speaker features a dual voice coil woofer and dual tweeters, allowing it to act as two speakers in one opening. It is perfect for providing L/R audio to small lavatories, entryways and hallways. **Features:** •Dual 13mm mylar dome tweeters •6½" poly cone woofer with rubber surround •Rotating plastic clips for easy mounting to existing drop ceiling tile or drywall •Optional pre-construction bracket to ease new–construction installations **Specifications:** •Power capacity: 50W RMS (each channel) •Frequency response: 50Hz~20KHz •Impedance: 8ohm (each channel) •SPL: 91dB (W/M) **Dimensions:** •Outer frame diameter: 9" •Required cutout: 8" diameter •Mounting depth: 3" **•Sold individually**

Order #	Model #	Description	(ea.)
50-4667	BA-650CS	Ceiling speaker	$64.95
50-4668	BA-BK6C	Pre-construction bracket pair	12.95

breatheaudio™ Indoor/Outdoor Speaker Pairs

Highly versatile speakers include a base stand for bookshelf use, and a "U" bracket for wall mounting. Their rugged enclosures and stainless steel hardware make these suitable for outdoor use, while the superior quality components provide outstanding performance expected of a pair of bookshelf speakers. **Features:** •6½" poly woofer with rubber surround •13mm mylar tweeter •Gold plated connections **Specifications:** •Power capacity: 50W RMS •Frequency response: 55Hz~20KHz •Sensitivity: 89dB (W/M) •Impedance: 8ohm •Dimensions: 13" (H) x 7⅝" (W) x 7" (D) **•Sold in pairs**

Order #	Model #	Color	(pr.)
50-4670	BA-6500B	Black	$199.00
50-4671	BA-6500W	White	199.00

breatheaudio™ Resonate™ 6½" In–Wall Speaker Pair

Designed for use with the Elevate™ Whole Home Music System, this high performing in–wall speaker pair is perfect for any residential or small commercial distributed sound system. The micro perforated grill adds to the aesthetic beauty of these speakers, which may be painted to match any décor. **Features:** •Pivotal 20mm silk dome tweeter •6½" poly cone woofer with rubber surround •Rotating plastic clips for easy mounting to existing drywall **Specifications:** •Power capacity: 50W RMS •Frequency response: 50Hz~20KHz •Impedance: 8ohm •SPL: 91dB (W/M) **Dimensions:** •Outer frame: 12" (H) x 8¾" (W) •Required cutout: 11⅛" (H) x 7¾" (W) •Mounting depth: 3" **•Sold in pairs**

Order #	Model #	(pr.)
50-4666	BA-650I	$99.95

breatheaudio™ Resonate™ 6½" Ceiling Speaker Pair

Designed for use with the Elevate™ Whole Home Music System, this high performing ceiling speaker pair is perfect for any residential or small commercial distributed sound system. The micro perforated grill adds to the aesthetic beauty of these speakers, which may be painted to match any décor. **Features:** •Pivotal 20mm silk dome tweeter •6½" poly cone woofer with rubber surround •Rotating plastic clips for easy mounting to existing drop ceiling tile or drywall •Optional pre-construction bracket to ease new–construction installations **Specifications:** •Power capacity: 50W RMS •Frequency response: 50Hz~20KHz •Impedance: 8ohm •SPL: 91dB (W/M) **Dimensions:** •Outer frame diameter: " •Required cutout: 8" diameter •Mounting depth: 3" **•Sold in pairs**

Order #	Model #	Description	(pr.)
50-4665	BA-650C	Speaker pair	$99.95
50-4668	BA-BK6C	Pre-construction bracket pair	12.95

breatheaudio™ Single Stereo Indoor/Outdoor Speaker

Often times a pair of outdoor speakers is impractical or undesired. In some areas, actual stereo imaging may not be a possibility, yet both channels need to be heard. This speaker features a dual voice coil woofer and two tweeters, allowing it to provide both left and right channels from a single point. Highly versatile speakers include a base stand for bookshelf use, and a "U" bracket for wall mounting. Their rugged enclosures and stainless steel hardware make these suitable for indoor or outdoor use. **Features:** •6½" poly woofer with rubber surround •Dual 13mm mylar tweeters •Gold plated connections **Specifications:** •Power capacity: 40W RMS (each channel) •Frequency response: 60Hz~20KHz •Sensitivity: 88dB (W/M) •Impedance: 8ohm (each channel) •Dimensions: 13" (H) x 7⅝" (W) x 7" (D) **•Sold individually**

Order #	Model #	Color	(ea.)
50-4672	BA-650-OSB	Black	$105.00
50-4673	BA-650-OSW	White	105.00

MCM 1-800-543-4330 Fax 1-800-765-6960



#50-4610, 50-4620



#50-4630

Stellar Labs™ Contractor Series Stereo Power Amplifiers

Designed specifically for use in distributed audio installations. Remote on/off triggering and signal sensing allow these units to be set up in equipment racks, with no further contact required. Rear mounted master level controls keep installation safe from future tampering. Two auto-switching inputs allow automatic operation when used with more than one system. **Features:** •Front panel controls for level, balance and A/B speaker selection •Two sets of L/R inputs, each may be switched to accept line level speaker level signal •Auto-switching between inputs, with adjustable delay •Line level pass through output on input #2 •Manual or auto-sensing power control •12V trigger input allows power-on command from external components •12V trigger output allows amplifier to trigger external components •Stereo and bridged mono operation •Heavy-duty binding post speaker outputs •Discrete output components •THD of less than 0.2% (at 4ohm) •See www.mcmelectronics.com for complete details including instruction manual

Order #	Model	Output (RMS @ 4ohm)	Output (8ohm) Bridged	MSRP	(ea.)
50-4610	SLA150	75W RMS x 2CH	150W RMS	$449.00	$209.00
50-4620	SLA250	125W RMS x 2CH	250W RMS	599.00	293.00
50-4630	SLA470	150W RMS x 2CH	470W RMS	799.00	186.00
CLEARANCE					

JobSite Two Channel Distributed Audio Amplifier

45W x two channel amplifier is perfect for amplifying a single zone in a distributed audio system. Multiple turn-on modes allow this amplifier to be left virtually unattended after installation. Output stages are stable to loads as low as 2.66ohm, allowing connection of up to three pairs of 8ohm speakers. Cascade line level outputs allow daisy chaining of multiple amplifiers. **Features:** •RCA line level inputs •Binding post speaker outputs •Independent gain control on each channel •Auto power on input sensing •3~30VAC/DC trigger input •12VDC trigger output **Specifications:** •Power output: 45W RMS x 2 channels •Frequency response: 10Hz~100KHz •S/N ratio: >85dB •Dimensions: 2⅝" (H) x 17" (W) x 13⅛" (D)

Order #	(ea.)
50-8585	$275.00

JobSite Audio Amplifier with Automatic Speaker Switch

Model AB50-X2, compact stereo amplifier, provides 50W x two channels and includes an automatic speaker selector circuit. This is especially useful if a distributed audio system exists, and a need arises to add a local line level source to only one local zone. **Features:** •RCA line level inputs •Snap lock speaker output connections •Gain control •Auto power on input sensing •3~30VAC/DC trigger input •12VDC trigger output •4ohm stable outputs **Specifications:** •Power output: 50W RMS x 2 channels •Frequency response: 5Hz~50KHz •S/N ratio: >85dB •Dimensions: 2¼" (H) x 8" (W) x 7½" (D) •Mfr. #AB50-X2

Order #	(ea.)
50-8590	$230.00

JobSite Volume Control Connection Terminal

This terminal block functions as a convenient hub for home run wiring. Connections are provided for up to eight impedance matching volume controls, with a single output pair for connection to the amplifier. Passive device requires no power. **Features:** •100W RMS per channel power handling capability •Snap and lock connectors accept up to 14AWG wire •Dimensions: 3" (H) x 6⅞" (W) x 1¼" (D)

Order #	(ea.)
50-8665	$42.95

JobSite 12 Channel Distributed Audio Amplifier

12 independent amplifier channels allow music to be distributed to up to six zones, making this perfect in distributed audio applications. Each amplifier channel may use its own line level input, or be switched to the common stereo input bus. Each channel has 30W RMS output, and adjacent channel pairs may be bridged for a single 80W RMS output channel. Amplifier outputs are stable to loads as low as 2.66ohm, allowing up to three 8ohm speakers to be paralleled to each channel. **Features:** •RCA line level inputs •Binding post speaker outputs •Bus input and output for cascading multiple amplifiers •Independent gain control on each channel •Auto power on input sensing •3~30VAC/DC trigger input •12VDC trigger output **Specifications:** •Power output: 30W RMS x 12 channels •Frequency response: 5Hz~50KHz •S/N ratio: 85dB •Dimensions: 5½" (H) x 17" (W) x 15" (D)

Order #	(ea.)
50-8580	$721.00

#50-8470

#50-8475

JobSite Speaker Selectors

Table top selectors are ideal for distributed audio systems where multiple speaker pairs are to be connected to a single amplifier. Available in four or six zone configurations, with or without volume controls for each zone. **Features:** •Switchable resistor type impedance protection, allowing full frequency response •Detachable snap-lock connectors •Custom room labels •Non-skid rubber feet •12-step rotary volume controls on each zone (applicable models) •100W per channel power capacity **Specifications:** •Frequency response: 20Hz~20KHz •Minimum impedance to amplifier: 8ohm

Order #	Mfr. #	Zones	Volume Controls	(ea.)
50-8470	S4	four	no	$84.95
50-8471	S6	six	no	115.00
50-8475	S4VC	four	yes	239.00
50-8476	S6VC	six	yes	285.00

JobSite Six Zone Distributed Audio Receiver

The M-64 multi-zone receiver utilizes 12 independent amplifier channels to distribute audio to six stereo zones. Each zone may independently select from up to four separate sources (including internal AM/FM tuner), and selection may be done either on the front panel, or via remote mounted keypad controllers. Multiple M-64 receivers may be cascaded to allow additional zones. **Features:** •Internal AM/FM stereo tuner with 20 presets •12 amplifier channels with 30W RMS per channel •Output channels are stable to 4ohm •Four input sources can be selected in any of six zones •Utilizes JobSite keypads and remotes •Includes one IR remote control •Individual fixed and variable preamp outputs for each zone •12VDC control output •Paging input •Dimensions: 5½" (H) x 17" (W) x 15" (D) •See www.mcmelectronics.com for complete information and 45 page owners manual.

Order #	(ea.)
50-8560	$1545.00

JobSite Remote Zone Control Enhanced Keypad

Designed specifically for addition to the M-4KP control, this 16 button keypad provides enhanced control of source inputs. Numeric keys from 0~9, (+) and (-) allow direct entry of CD tracks, preset stations and similar functions. Additional keys are provided for RANDOM, GROUP, DISC and FAV functions. Unit occupies a single gang space in electrical boxes or low voltage brackets, and although it is ideally mounted in a double gang space with the M-4KP, it may me mounted alone. Keypad includes a short RJ-45 jumper for connection to the M-4KP. •Required depth: 2⅜" •Mfr. #M-10KP

Order #	(ea.)
50-8575	$55.95

JobSite Remote Zone Control Keypad

Single gang keypad mounts in standard electrical box or low voltage bracket, and allows source selection, on/off and volume control of the M-64 receiver from a remote location. Kit includes 200 key labels for custom source identification, as well as white, bone and almond decora plate inserts. **Features:** •Source-in-use indication •12 step volume control •Backlit keys •Three female RJ-45 connectors for connection to M-64 receiver, M10-KP enhanced keypad and IR remote input •Required depth: 2⅜" •Mfr. #M-4KP

Order #	(ea.)
50-8570	$94.95

JobSite IR Remote Control

42-button control provides complete wireless operation of the M-64 multi-zone receiver. Unit may be pointed directly at the M-64 receiver, or at remote mounted IR receivers. Requires two "AA" batteries (included). Dimensions: 8½" (H) x 2½" (W) x 1⅜" (D)

Order #	(ea.)
50-8565	$27.95

6½" Ceiling Speaker Pair

Perfect ceiling speaker for high performance music and voice reproduction. Suitable for use in bathrooms, kitchens and similar areas with potentially high moisture. **Features:** •6½" talc filled polypropylene woofer with urethane surround •¾" tweeter •Rustproof aluminum grill •Suitable for painting •Color coded push terminals accept up to 12AWG wire **Specifications:** •Power handing: 5~60W •Frequency response: 65Hz~20KHz •Impedance: 6ohm **Dimensions:** •Overall frame diameter: 9¼" •Required cutout: 8" •Mounting depth: 3⅜" •Mfr. #LSC-6 •**Sold in pairs**

Order #	(pr.)
50-8510	$165.00

5¼" Recessed Ceiling Speaker Pair

Perfect ceiling speaker for accurate music and voice reproduction. Unique recessed appearance provides the appearance of a recessed can light. Suitable for use in bathrooms, kitchens and similar areas with potentially high moisture. **Features:** •5¼" polypropylene woofer with urethane surround •½" tweeter •Rustproof aluminum grill •Suitable for painting •Color coded push terminals accept up to 12AWG wire **Specifications:** •Power handing: 3~50W •Frequency response: 75Hz~20KHz •Impedance: 8ohm **Dimensions:** •Overall frame diameter: 7¾" •Required cutout: 6½" •Mounting depth: 2¾" •Mfr. #LSC-5R •**Sold in pairs**

Order #	(pr.)
50-8505	$89.95

5¼" Ceiling Speaker Pair

Perfect ceiling speaker for accurate music and voice reproduction. Suitable for use in bathrooms, kitchens and similar areas with potentially high moisture. **Features:** •5¼" polypropylene woofer with urethane surround •¾" tweeter •Rustproof aluminum grill •Suitable for painting •Color coded push terminals accept up to 12AWG wire **Specifications:** •Power handing: 3~50W •Frequency response: 63Hz~20KHz •Impedance: 8ohm **Dimensions:** •Overall frame diameter: 7¾" •Required cutout: 6½" •Mounting depth: 2¾" •Mfr. #LSC-5 •**Sold in pairs**

Order #	(pr.)
50-8500	$89.95

6½" High Performance Ceiling Speaker Pair

Perfect speaker for high performance music reproduction in ceiling locations. Suitable for use in bathrooms, kitchens and similar areas with potentially high moisture. **Features:** •6½" injection molded polypropylene woofer with butyl rubber surround •1" pivoting soft dome tweeter •Rustproof aluminum grill •Suitable for painting •Color coded push terminals accept up to 12AWG wire **Specifications:** •Power handing: 10~125W •Frequency response: 50Hz~21KHz •Impedance: 4ohm or 8ohm selectable **Dimensions:** •Overall frame diameter: 9¼" •Required cutout: 8" •Mounting depth: 3⅜" •Mfr. #LSC-6.5 •**Sold in pairs**

Order #	(pr.)
50-8515	$197.00

6½" In–Wall Speaker Pair

Perfect speaker for high performance music and voice reproduction from wall locations. Suitable for use in bathrooms, kitchens and similar areas with potentially high moisture. These speakers are suitable for horizontal or vertical mount in wall surfaces and vaulted ceilings. **Features:** •6½" talc filled polypropylene woofer with urethane surround •¾" pivotal dome tweeter •Rustproof aluminum grills•Suitable for painting •Color coded push terminals accept up to 12AWG wire •Knockout for JobSite flush mount IR receiver **Specifications:** •Power handling: 10~75W •Frequency response: 65Hz~20KHz •Impedance: 8ohm **Dimensions:** •Overall frame: 11$^{1}\!/_{16}$" (H) x 8¾" (W) •Required cutout: 10⅝" (H) x 7⅞" •Mounting depth: 3⅜" •Mfr. #LSW-6 •**Sold in pairs**

Order #	(pr.)
50-8525	$165.00

8" Ceiling Speaker Pair

Perfect ceiling speaker for high performance music and voice reproduction. Suitable for use in bathrooms, kitchens and similar areas with potentially high moisture. **Features:** •8" talc filled polypropylene woofer with treated foam rubber surround •¾" tweeter •Rustproof aluminum grill •Suitable for painting •Color coded push terminals accept up to 12AWG wire **Specifications:** •Power handing: 5~100W •Frequency response: 55Hz~20KHz •Impedance: 6ohm **Dimensions:** •Overall frame diameter: 10⅝" •Required cutout: 9½" •Mounting depth: 3¾" •Mfr. #LSC-8 •**Sold in pairs**

Order #	(pr.)
50-8512	$232.00

6½" Single Stereo Ceiling Speaker

Perfect for high performance music reproduction in ceiling locations, this speaker features a dual voice coil woofer, and dual tweeters, for stereo music reproduction from a single point. It is perfect in small areas where two speakers are not practical. While this appears as one speaker to the listener, it appears as two independent speakers to the amplifier system. It is suitable for use in bathrooms, kitchens and similar areas with potentially high moisture. **Features:** •6½" talk filled polypropylene woofer with butyl rubber surround •Dual ½" stereo imaged liquid cooled dome tweeters •Rustproof aluminum grill •Suitable for painting •Color coded push terminals accept up to 12AWG wire **Specifications:** •Power handing: 10~100W per channel •Frequency response: 60Hz~21KHz •Impedance: 6ohm per channel **Dimensions:** •Overall frame diameter: 9¼" •Required cutout: 8" •Mounting depth: 3⅜" •Mfr. #LSC-6S •**Sold individually**

Order #	(ea.)
50-8520	$93.95

6½" High Performance In-Wall Speaker Pair

Perfect speaker for high performance music and voice reproduction from wall locations. Suitable for use in bathrooms, kitchens and similar areas with potentially high moisture. These speakers are suitable for horizontal or vertical mount in wall surfaces and vaulted ceilings. **Features:** •6½" polypropylene woofer with butyl rubber surround •1" pivotal soft dome tweeter •Rustproof aluminum grill •Suitable for painting •Color coded push terminals accept up to 12AWG wire •Knockout for JobSite flush mount IR receiver **Specifications:** •Power handing: 10~125W •Frequency response: 50Hz~21KHz •Impedance: 6ohm **Dimensions:** •Overall frame: 11$^{1}\!/_{16}$" (H) x 8¾" (W) •Required cutout: 10⅝" (H) x 7⅞" (W) •Mounting depth: 3⅜" •Mfr. #LSW-6.5 •**Sold in pairs**

Order #	(pr.)
50-8530	$275.00

6½" Home Theater In-Wall Speaker

Perfect speaker for high performance music reproduction from wall locations, these are also ideal as main or surround speakers in typical home theater environments. Suitable for use in areas with potentially high moisture, these speakers are intended for vertical mount. **Features:** •Dual 5¼" mica filled polypropylene woofers with butyl rubber surrounds •1" liquid cooled dome tweeter **Specifications:** •Power handing: 10~150W •Frequency response: 45Hz~21KHz •Impedance: 8ohm **Dimensions:** •Overall frame: 14½" (H) x 8¼" (W) •Required cutout: 13¼" (H) x 7⅛" (W) •Mounting depth: 2⅝" •Mfr. #LST-RLS •**Sold individually**

Order #	(ea.)
50-8535	$184.00

6½" Center Channel In-Wall Speaker

Perfect for high performance music reproduction, this unit is designed for center channel use. Magnetically shielded woofers and tweeter enable close proximity to any type of video display device. Narrow driver arrangement allows installation between 16" spaced studs. **Features:** •Dual 5¼" mica filled polypropylene woofers with butyl rubber surrounds •1" liquid cooled dome tweeter •Dialog selector •3dB high frequency cut selector **Specifications:** •Power handing: 10~150W •Frequency response: 45Hz~21KHz •Impedance: 8ohm **Dimensions:** •Overall frame: 14½" (W) x 8¼" (H) •Required cutout: 13¼" (W) x 7⅛" (H) •Mounting depth: 3⅜" •Mfr. #LST-CTR •**Sold individually**

Order #	(ea.)
50-8540	$198.00



Ceiling Speaker Pre-Construction Bracket Pairs

Specifically designed for Niles/JobSite ceiling speaker models, these rugged bracket assemblies greatly ease installation of ceiling speakers in new construction applications. Simply attach to ceiling joists prior to drywall installation for easy location and secure mounting of speaker systems during final installation. ⅜" lip provides perfect finished edge for drywall thickness. Removable wings allow screw or nail mounting to virtually any stud or joist spacing. **Sold in pairs.**

Order #	Mfr. #	Compatible speaker size	(pr.)
50-8555	NCB-6	6½"	$25.95
50-8556	NCB-5	5¼"	21.95
50-8557	NCB-8	8"	29.95

MCM
1-800-543-4330
Fax 1-800-765-6960

Single Zone IR Connecting Block

Intended as the hub of the complete JobSite Plasma proof IR repeater system, this connecting block provides point of connection for emitters, receivers and power supply. **Features:** •Single zone control •Single IR receiver input •Four IR emitter outputs •Snap lock receiver inputs •3.5mm emitter outputs •Includes UL listed 12VDC power supply •Dimensions: 1¼" (H) x 4¾" (W) x 2" (D) •Mfr. #IR-CB1

Order #	(ea.)
50-8615	$52.95

Two Zone IR Connecting Block



Intended as the hub of the complete JobSite Plasma proof IR repeater system, this connecting block provides point of connection for emitters, receivers and power supply. **Features:** •Two zone control •Two IR receiver inputs •Five IR emitter outputs •Selectable high/low emitter output for use with high output, single and dual emitters •Snap lock receiver inputs •3.5mm emitter outputs •Includes UL listed 12VDC power supply •Dimensions: 1¼" (H) x 5⅛" (W) x 2" (D) •Mfr. #IR-CB2

Order #	(ea.)
50-8620	$64.95

Four Zone IR Connecting Block



Intended as the hub of the complete JobSite Plasma proof IR repeater system, this connecting block provides point of connection for emitters, receivers and power supply. **Features:** •Four zone control •Four IR receiver inputs •Eight IR emitter outputs •Selectable high/low emitter output for use with high output, single and dual emitters •12VDC output for sensing status or discrete IR commands •Contact closure triggered by sensing status or discrete IR commands •Snap lock receiver inputs •3.5mm emitter outputs •Includes UL listed 12VDC power supply •Dimensions: 1¼" (H) x 7⅛" (W) x 3" (D) •Mfr. #IR-CB4

Order #	(ea.)
50-8625	$89.95

Six Zone IR Connecting Block Expander

Increases a single input on the JobSite connecting block from one to six. Greatly reduces clutter in areas where numerous IR sensors are placed some distance from the connecting block. Instead of home running all sensors to the block, they can be hubbed at this expander, with a single run to the block. **Features:** •Snap lock connectors •Six IR receiver inputs •Talkback LED indicates system status •Dimensions: 1¼" (H) x 7⅛" (W) x 1¼" (D) •Mfr. #IR-CBE6

Order #	(ea.)
50-8630	$49.95

Compact Surface Mount IR Receiver

Plasma proof IR receiver rejects interference common of flat panel displays, CFL lighting and indirect sunlight. Simple self-adhesive surface mounting allows the unit to be located on virtually any smooth clean surface. **Features:** •Red status LED •Blue talkback LED •Receiving range: 18'~30' depending remote •Works up to 30° off axis •Black color •Includes attached 10' connecting cable •Requires two pairs of Cat 5 or higher wire •Dimensions: ½" (H) x 1⅛" (W) x 2⅛" (D) •Mfr. #IR-SMR

Order #	(ea.)
50-8605	$87.95

High Output IR Emitter

Designed to provide IR signal to source equipment from remote location, high output emitter mounts inside equipment racks and floods the entire cavity with the IR pulse, thus controlling all equipment in the rack. This serves as a suitable alternative to locating individual emitters on every piece of equipment. **Features:** •10' attached cable terminated with a 3.5mm two conductor plug •Emits IR signal up to 18'~30' line of sight •Peel-and-stick self adhesive mounting •Dimensions: ⅜" (H) x 1" (W) x 2¼" (D) •Mfr. #IR-E1HO

Order #	(ea.)
50-8640	$22.50

IR Emitter

Designed to provide IR signal to source equipment from remote location, this emitter attaches directly to the IR window on system equipment. Specially designed pass-through housing does not block IR window, allowing local control as normal. **Features:** •10' attached cable terminated with 3.5mm two conductor plug •Cable length may be increased up to 40' with 18AWG cable •Cable length may be increased up to 200' with 16AWG cable •Emits IR signal up to 48" line of sight •Peel-and-stick self adhesive mounting •Ultra compact size: 3/16" (H) x 3/16" (W) x ½" (D) •Mfr. #IR-E1

Order #	(ea.)
50-8635	$8.99

Dual IR Emitter

Identical to #50-8635 with dual emitters. Dual emitters on a single plug increase the total number of emitters that may be connected to a single control block. •Mfr. #IR-E2

Order #	(ea.)
50-8636	$16.25

All Weather Stereo In-Wall Volume Control

Designed for use in distributed audio systems, primarily those involving outdoor and landscaping (rock) speaker systems, as well as in-wall and ceiling speakers in high humidity environments. Impedance matching design allows of up to 16 pairs of 8ohm speakers to be connected to a single stereo amplifier, and appear as a 4ohm load. **Features:** •Snap-lock connectors accept up to 14AWG wire •Includes both decora and standard cover plates **Specifications:** •Power capacity: 100W/200W RMS/peak

Order #	(ea.)
50-8648	$54.95

Complete IR Repeater Kit

Complete plasma proof IR repeater kit includes all necessary components for control of up to five devices from a remote location. **Kit includes:** •One IR-CB2 connecting block with power supply •Five IR-E1 emitters •One IR-SMR IR receiver •Mfr. #IR-KIT

Order #	(kit)
50-8610	$198.00

Wall Mount IR Receivers

Plasma proof IR receiver rejects interference common of flat panel displays, CFL lighting and indirect sunlight. Single gang decora style mounts in standard electrical boxes or low voltage brackets and may be combined with other low voltage devices behind a multiple gang decora plate. **Features:** •Extended receiving range •Red status LED •Blue talkback LED •Snap-and-lock connector •Includes matching decora faceplate •Requires two pairs of Cat 5 or higher wire •Depth behind faceplate: 2¾" •Mfr. #IR-WMR

Order #	Color	(ea.)
50-8591	White	$68.95
50-8592	Bone	65.00
50-8595	Almond	65.00

Flush Mount IR Receiver

Plasma proof IR receiver rejects interference common of flat panel displays, CFL lighting and indirect sunlight. Compact flush mount design is perfect for installation into wall plates, entertainment system panels or any other flat surface. All JobSite in-wall speaker systems include a knock-out for installation of this receiver. **Features:** •Receiving range: 18'~30' depending remote •Works up to 30° off axis •Includes black and white bezels •Includes attached 10' connecting cable •Requires two pairs of Cat 5 or higher wire •Front bezel diameter: ¾" •Required mounting hole: ½" •Mounting depth: 2⅝" •Mfr. #IR-FMR

Order #	(ea.)
50-8600	$94.95

Stereo In-Wall Volume Controls

In-wall volume controls utilize high quality multitap audio transformers and smooth 12 position rotary switches to provide full range level control. They are designed for use in distributed audio systems, primarily those involving in-wall and ceiling speaker systems. Impedance matching design allows up to 16 pairs of 8ohm speakers to be connected to a single stereo amplifier, and appear as a 4ohm load. **Features:** •Snap-lock connectors accept up to 14AWG wire •Includes both decora and standard cover plates •May be mounted in a single gang box or low voltage bracket **Specifications:** •Power capacity: 100W/200W RMS/peak •Impedance matching settings: x1, x2, x4 and x8

Order #	Color	(ea.)
50-8645	White	$35.95
50-8646	Bone	35.95
50-8647	Ivory	35.95

SpeakerCraft® Impedance Matching Volume Control

These stereo in-wall volume controls are designed for use in distributed audio systems, primarily with in-wall and ceiling speakers. Impedance matching design enables up to 8 pairs of 8ohm speakers to be connected to a stereo amplifier, and appear as a 4ohm load. Decora style face plate is compatible with standard decora single and multi gang covers. Single gang cover is included. Unit is shipped as white color,hardware and knobs are included for conversion to bone or almond. **Features:** •Detachable terminal strip, greatly easing installation •Fits standard electrical boxes and low voltage brackets •Ten step attenuation **Specifications:** •Power capacity: 45W RMS •Frequency response: 20Hz~20KHz •Overall depth: 2½"

Order #	(1-3)	(4-11)	(12-up)
50-8220	$31.44	$29.13	$26.04

SpeakerCraft® Audiophile Grade In-Wall Volume Controls



These stereo volume controls are designed for use in distributed audio systems, primarily with in-wall and ceiling speakers. Resistor based design provides much improved frequency response when compared to conventional transformer based units. Specially selected non-inductive, high capacity resistors ensure full frequency response, with less than 0.5dB variance. Decora style face plate is compatible with standard decora single and multi gang covers. Single gang cover is included. Unit is shipped as white color, hardware and knobs are included for conversion to bone or almond. **Features:** •Available in 60W and 120W RMS models •Special push-lock connector for fast connection without a screwdriver •Fits standard electrical boxes and low voltage brackets •12 step attenuation **Specifications:** •Frequency response: 20Hz~20KHz, < ±0.5dB •Overall depth: 2½"

Order #	Power Capacity	(1-3)	(4-11)	(12-up)
50-8230	60W RMS	$34.95	$33.19	$29.59
50-8240	120W RMS	39.95	36.95	33.95

SpeakerCraft® Free Standing Stereo Volume Control

Intended for use when in-wall type controls are not practical, this control is ideal for use with free standing remote speaker systems. **Features:** •Removable terminal strip for greatly eased installations •12 step attenuation •Suction cup feet to hold the unit secure during use **Specifications:** •Power capacity: 60W RMS •Frequency response: 20Hz~20KHz •Dimensions: Overall depth: 2.19" (H) x 8.5" (W) x 6.5" (D) •Call for larger quantity pricing

Order #	(1-3)	(4-11)	(12-up)
50-8275	$92.95	$87.60	$78.80

SpeakerCraft® Impedance Matching Volume Control

These stereo in-wall volume controls are designed for use in distributed audio systems, primarily with in-wall and ceiling speakers. Impedance matching design enables up to 18 pairs of 8ohm speakers to be connected to a stereo amplifier, and appear as a 4ohm load. Decora style face plate is compatible withstandard decora single and multi gang covers. Single gang cover is included. Unit is shipped as white color, hardware and knobs are included for conversion to bone or almond. **Features:** •LiftLock™ connector, enables fast connection without a screwdriver •Fits standard electrical boxes and low voltage brackets •12 step attenuation **Specifications:** •Power capacity: 60W RMS •Frequency response: 20Hz~20KHz •Overall depth: 2½"

Order #	(1-3)	(4-11)	(12-up)
50-8200	$49.95	$47.50	$44.95

SpeakerCraft® In-Wall Volume Control



These stereo volume controls are designed for use in distributed audio systems, primarily with in-wall and ceiling speakers. Decora style face plate is compatible with standard decora single and multi gang covers. Single gang cover is included. Unit is shipped as white color, hardware and knobs are included for conversion to bone or almond. **Features:** •LiftLock™ connector, enables fast connection without a screwdriver •Fits standard electrical boxes and low voltage brackets •12 step attenuation **Specifications:** •Power capacity: 60W RMS •Frequency response: 20Hz~20KHz •Overall depth: 2½"

Order #	(1-3)	(4-11)	(12-up)
50-8210	$39.95	$37.75	$33.95



SpeakerCraft® Parallel Connecting Blocks

Ends the problem of multiple speaker home runs to a single location. The CB connecting block enables easy connection of four pairs of speakers, to a single bus. This bus then is easily connected to the amplifier output. The CBX expansion blocks can then be added to the connecting block, providing connection for four additional pairs. An endless number of CBX blocks may be cascaded on a single CB block. Compact units have screw holes for attaching inside the wall, to a stud. **Note:** This is a straight parallel connection and no impedance protection is provided. Impedance matching volume controls must be used if the overall impedance falls below the minimum level of the amplifier.

Order #	Description	(1-3)	(4-11)	(12-up)
50-8305	CB connecting block	$34.50	$31.95	$29.33
50-8306	CBX expansion block	31.50	28.95	26.78

SpeakerCraft® Multi–Zone Speaker Selectors

Ideal for controlling multiple pairs of installed speaker systems from a single location. Four and eight zone models are available with simple pushbutton on/off control for each zone. Four and six zone versions feature on/off selectors as well as 12 step volume controls for each zone. **Features**: •Rugged 17" wide metal housing (S4DC is 8⅜") •Front panel impedance protection switch, with rear panel override •Suction feet to hold unit firmly to shelf during use •Removable screw terminal connections accept up to 14AWG wire •100 room labels to customize to any application **Specifications:** •Power capacity: 125W RMS per channel (all zones combined) •Frequency response: 20Hz~20KHz ±0dB •Dimensions (S4DC): 2⅜" (H) x 8⅜" (W) x 6½" (D) •Dimensions (others): 2⅜" (H) x 17" (W) x 6½" (D)

Order #	Mfr. #	Description	(1–3)	(4–11)
50-8400	S8DC	Eight zone	$250.00	$237.50
50-8405	S4DC	Four zone	150.00	142.50
50-8430	S6VC	Six zone with volume controls	425.00	403.75
50-8435	S4VC	Four zone with volume controls	350.00	332.50

SpeakerCraft® Outdoor Volume Controls

Specifically designed for outdoor applications, these volumes controls feature stainless steel hardware and a PVC enclosure, and are ideally suited for use with landscaping "rock" speaker systems. The housing attaches to standard ¾" PVC conduit for simplified watertight installation. Resistor based design provides improved frequency response when compared to conventional transformer based units. Specially selected non-inductive, high capacity resistors ensure full frequency response, with less than 0.5dB variance. **Features:** •Special push-lock connector for fast connection without a screwdriver •Fits standard electrical boxes and low voltage brackets •12 step attenuation **Specifications:** •Power capacity: 60W •Frequency response: 20Hz~20KHz, < ±0.5dB •Overall depth: 2½" •Call for larger quantity pricing

Order #	Color	(1-3)	(4-11)	(12-up)
50-8270	Gray	$74.95	$68.49	$61.75
50-8271	White	74.95	68.49	61.75

SpeakerCraft® In–Wall A/B Speaker Switch

Simple pushbutton A/B operation allows selection of two speaker pairs from a single amplifier, or a single pair of speakers to select between two separate sources. Ideal when a pair of in–wall or ceiling speakers is needed for a local stereo or home theater system, and whole house audio. Mounts in standard single gang electrical boxes or low voltage brackets, units include decora cover plate and all hardware.

Order #	Description	(1–3 kits)	(4–11 kits)
50-8440	White	$34.95	$33.20
50-8441	Bone	34.95	33.20
50-8442	Almond	34.95	33.20
50-8443	Black	34.95	33.20

SpeakerCraft® Octagonal Light Collector Lens

IR lens is designed to attach to equipment or remote mounted IR receivers to improve reliability of IR reception. Multi-array mirror system provides 90° reflection angle, insuring equipment will "see" the IR emitter. Sold in packages of ten.

Order #	Mfr. #	(1-3 pkgs.)	(4-11 pkgs.)	(12 pkgs.-up)
50-8370	ILC-1.0	$18.00	$17.10	$15.30

MCM 1-800-543-4330 Fax 1-800-765-6960

SpeakerCraft SmartPath Infrared Repeating System

SmartPath's easy installation and configuration allow installers to quickly create a pathway of complete A/V system control. All components are available separately for versatile configuration of any custom system. Emitters and receivers may be connected with two pairs of 24AWG solid or stranded unshielded twisted pair wire, including standard Cat5, for distances up to 1200'. Heavier gauge cable can be used for distances of up to 5000'. *A complete system requires the following four basic components:* •At least one infrared receiver •One connecting block •As many emitters as needed to control A/V components •One DC power supply

SpeakerCraft Wall Mount "Junction Box" IR Receivers

Attractive receivers include clearly visible system status and IR activity LEDs, to provide positive feedback to the user, and mount in standard single gang junction boxes or low-voltage brackets. Decora style design is compatible with standard wall plates, single gang plate is included. EZ-connector terminal block allows simple connection of unterminated twisted pair wire. Dimensions: 4" (H) x 1½" (W) x 1" (D)

Order #	Mfr. #	Color	(1-3)	(4-11)	(12-up)
50-8330	IRC-4.0	White	$116.25	$110.50	$98.75
50-8331	IRC-4.0	Bone	110.00	104.50	93.50
50-8332	IRC-4.0	Almond	110.00	104.50	93.50

SpeakerCraft Ultra Compact Plasma Block Mini IR Receivers



These units are designed to block plasma, CFL, EMI, and ESI noise sources, using SpeakerCraft's exclusive "smart" circuit (patent pending). The actual sensor and electronics are separated into separate "main" and "pick-up" modules, enabling installation into very tiny spaces of furniture recesses, monitor panels and under shelves. The main module houses the status and activity LEDs. Detachable lead between main and pick-up module totals 6' in length. The main module has attached 5' lead, terminated with bare wire connections or SpeakerCraft's unique four-conductor 3.5mm plug. Overall reception angle is 100°. Dimensions:
•Pick-up module: ⅜" (L) x 13/32" (W) x 3/32" (D)
•Main module: 2 9/16" (L) x 9/16" (W) x ½" (D)

Order #	Mfr. #	Connection	(1-3)	(4-11)	(12-up)
50-8320	IRC-2P2.0	3.5mm plug	$115.00	$105.00	$95.00
50-8321	IRC-2P2.1	Bare leads	115.00	105.00	95.00

SpeakerCraft Emitter Expansion Terminator

The EMX-1.0 expansion terminator expands the number of outputs of the AT-1.0 amplified terminator unit. This passive device simply plugs into the emitter output of the AT-1.0, and provides up to ten emitter outputs. A feed through output is also provided, allowing multiple EMX-1.0s to be cascaded. Includes 12" cable for connection to the AT-1.0.

Order #	Mfr. #	(1-3)	(4-11)
50-8350	EMX-1.0	$21.95	$19.99

SpeakerCraft Break Out Terminator

The BOT-1.0 breakout terminator provides bare wire connection to SmartPath IR receivers that are equipped with SpeakerCraft's standard four-conductor 3.5mm plug. This allows plug terminated receivers to be connected to the EZ-connect terminal blocks, as well as other brand three and four wire systems.

Order #	Mfr. #	(1-3)	(4-11)
50-8345	BOT-1.0	$9.29	$8.82

SpeakerCraft Flush Mount Mini IR Receivers



Compact receivers require only a ½" hole, and may be mounted flush in cabinets or walls, leaving only a circular bezel exposed to the room. They may also be mounted behind the grill of most in-wall speakers. Each includes a set of four color bezels (almond, black, bone and white), to match any décor. Also included are two specially designed ALR (ambient light restrictor) bezels, for use near plasma displays. Clearly visible system status and IR activity LEDs provide positive feedback to the user. Models include an 8' attached lead, and are available with bare wire connections or SpeakerCraft's unique four-conductor 3.5mm plug. Receivers provide a reception angle of 110° standard, 60° with ALR bezel installed. **Dimensions:**
•Unit: 15/32" diameter x 2⅝" (L) •Cap bezel: 47/64" diameter x ⅛" (L) •ALR bezel: 47/64" diameter x 2 39/64" (L)

Order #	Mfr. #	Connection	(1-3)	(4-11)	(12-up)
50-8310	IRC-1.0	3.5mm plug	$126.10	$120.00	$107.25
50-8311	IRC-1.1	Bare leads	127.00	119.95	107.25

SpeakerCraft Surface Mount Mini IR Receivers

Compact receivers are intended for surface mounting on cabinets, TV sets or the wall, with attached double sided adhesive. Clearly visible system status and IR activity LEDs provide positive feedback to the user. Models are available in black or white, with 8' attached lead, terminated with bare wire connections or SpeakerCraft's unique four-conductor 3.5mm plug. Black version, with stripped leads is also available with the ALR (ambient light restrictor) lens for use near plasma displays. Standard receivers provide a reception angle of 110°, the ALR version is 60°. Dimensions: 2 9/16" (L) x 13/32" (W) x 3/16" (L)

Order #	Mfr. #	Color	Connection	(1-3)	(4-11)	(12-up)
50-8315	IRC-2.0	White	3.5mm plug	$121.00	$115.25	$103.15
50-8316	IRC-2.0	Black	3.5mm plug	121.00	115.25	103.15
50-8317	IRC-2.1	White	Bare leads	121.00	115.25	103.15
50-8318	IRC-2.1	Black	Bare leads	127.60	121.35	108.95
50-8319	IRC-2.1 ALR	Black	Bare leads	127.65	121.35	108.75

SpeakerCraft High Power IR Blaster

Designed for installation into equipment rack, this unit is intended to provide sufficient output to control all components. The unique 3" wand features two high output IR emitters "flooding" the rack with the remote signal. The wand can be adjusted above or below a rack of components to suit specific situation. Attached 8' lead is terminated with a two-conductor 3.5mm plug.

Order #	Mfr. #	(1-3)	(4-11)	(12-up)
50-8360	IRE-5.0	$29.50	$28.03	$25.08

SpeakerCraft Complete SmartPath IR Repeater System

Take the guess work out of setting up a typical one room system with this complete IR repeater kit, everything is included in one convenient package. **System includes:** •One IRC-3.0 shelf top receiver •One AT-1.0 amplified terminator unit •One PS-1.0 power supply •Four IRE-1.0 IR emitters

Order #	Mfr. #	(1-3)	(4-11)
50-8363	IRC-3.0 KIT	$215.00	$204.00

SpeakerCraft Shelf Top IR Receivers

Compact receivers are housed in an attractive case to sit on the surface of a cabinet or shelf. Clearly visible system status and IR activity LEDs provide positive feedback to the user. Models include an 8' attached lead, terminated with SpeakerCraft's unique four-conductor 3.5mm plug. Unit is available in standard configuration, or with the ALR (ambient light restrictor) bezels, for use near plasma displays. Standard receivers provide a reception angle of 110°, ALR version is 60°. Dimensions: 1⅛" (L) x 3 3/16" (W) x 1⅛" (D)

Order #	Mfr. #	(1-3)	(4-11)	(12-up)
50-8325	IRC-3.0	$75.00	$71.25	$63.75
50-8326	IRC-3.0 ALR	75.00	71.25	63.75

SpeakerCraft Amplified Terminator Unit

The AT-1.0 amplified terminator unit functions as central control unit for large multi room IR systems, allowing connection of the power supply, IR emitters and receivers. EZ-connect terminal block allows connection of multiple daisy chained receivers. Four-conductor 3.5mm jack accepts connection of one similarly equipped receiver. This unit has a total of four outputs that will drive four emitters, or two emitters and two blasters. The EMX-1.0 expansion terminator (#50-8350) allows connection of additional emitters. 5~24VDC status input accepts status signal from IR controlled equipment, and provides visual indication at each IR receiver.

Order #	Mfr. #	(1-3)	(4-11)	(12-up)
50-8335	AT-1.0	$79.95	$75.95	$67.95

SpeakerCraft Passive Terminator

The PT-1.0 passive terminator functions as central control unit for compact, single room IR systems, allowing connection of the power supply, up to two IR emitters and a single IR receiver, equipped with a four-conductor 3.5mm plug. 5~24VDC status input accepts status signal from IR controlled equipment, and provides visual indication at the IR receiver.

Order #	Mfr. #	(1-3)	(4-11)	(12-up)
50-8340	PT-1.0	$11.34	$10.65	$9.65

SpeakerCraft® Micro Mini IR Emitter

Extremely compact IR sensor is only slightly larger diameter than its connection cable, and can be placed inside the actual component, near the IR sensor. This emitter will "blast" the entire chassis, ensuring the equipment IR sensor will receive the signal. It is a great alternative to "untidy" front panel emitters. Includes 8' lead terminated with two-conductor 3.5mm plug.

Order #	Mfr. #	(1-3)	(4-11)	(12-up)
50-8355	IRE-0.5	$23.49	$21.95	$19.79

SpeakerCraft® SmartPath Connecting Cables

Use to adapt components for use with other equipment, or to extend existing leads. **Sets include: •PTP-1.0:** Set of six, 12" 2-conductor cables, male to male 3.5mm plugs **•PTP-8:** Set of six, 8' 2-conductor cables, male to male 3.5mm plugs **•PTJ-40:** 40' 2-conductor cable, male to female 3.5mm plugs **•QIX-1.0:** 15' 4-conductor cable, male to female 3.5mm plugs **•SAC-1.0:** Diode protected "Y" cable, single female to two male 3.5mm plugs, allows connection of one emitter to two sources **•PTS-3:** Set of six, 36" 2-conductor cables, male 3.5mm plug to stripped leads **•STS-4:** Set of six, 48" 2-conductor cables, barrel type power plug to stripped leads.

Order #	Mfr. #	(1-3 sets)	(4-11 sets)	(12 sets -up)
50-8372	PTP-1.0	$20.00	$19.00	$17.00
50-8373	PTP-8	32.95	30.45	27.20
50-8374	PTJ-40	49.95	47.50	42.50
50-8375	QIX-1.0	8.50	8.08	7.23
50-8376	SAC-1.0	8.99	8.57	7.69
50-8377	PTS-3	12.00	11.40	10.20
50-8378	STS-4	13.00	12.37	11.07

SpeakerCraft® SmartPath IR System Power Supplies

Supplies plug directly into SpeakerCraft terminator models AT-1.0 or PT-1.0 to provide power to the entire IR repeater system. Both high quality units are regulated at 12VDC, at the current rating shown below. The correct power supply, with sufficient current output, must be selected for the system in place. To calculate current requirements, simply add the current draw of each device to determine the total current needed. **Current draw of SpeakerCraft devices are as follows:** •IR emitters: 15mA •IR receivers: 6mA •IR blasters: 150mA •Terminator units AT-1.0 and PT-1.0 add no additional current draw

Order #	Mfr. #	Current	(1-3)	(4-11)
50-8361	PS-2.0	1200mA	$55.00	$52.25
50-8362	PS-1.0	200mA	13.00	12.35

SpeakerCraft® Standard IR Emitters

Compact sensors attach via included double sided adhesive, and may be mounted near equipment to be controlled. Multiple configurations are available to suit a variety of applications. Dual emitter units allow placement in front of two pieces of equipment, from only one plug connection. Units with visible LEDs provide visible feedback of presence of IR signal. Each includes an attached 8' lead, terminated with a two-conductor 3.5mm plug.

Order #	Mfr. #	Description	(1-3)	(4-11)	(12-up)
50-8356	IRE-1.0	Single emitter	$11.59	$10.89	$10.09
50-8357	IRE-2.0	Dual emitter	21.95	19.95	17.95
50-8358	IRE-3.0	Single emitter w/visible LED	11.59	10.89	10.09
50-8359	IRE-4.0	Dual emitter w/visible LED	19.95	18.95	16.95

SpeakerCraft® Emitter Cover

Prevents IR signals from interfering with other components. Fits over SmartPath IR emitters or components IR sensor window. Units measure 1" x 2" and may be trimmed to fit.

Order #	Mfr. #	(1-3)	(4-11)	(12-up)
50-8371	IR SHIELD	$2.00	$1.90	$1.70



MCM CUSTOM AUDIO Keystone Mount 3.5mm Connector

This keystone insert features a standard 3.5mm three-conductor female jack which may be used in two or three conductor applications. It is ideal any time a 3.5mm connector is needed at a wall plate. Rear mounted IDC connector allows simple, fast connection to unterminated Cat 5 cable, or any 22~24AWG solid or stranded, UTP or shielded wire. Maximum voltage: 24VAC/DC, 1A. **Applications:** •Remote location of headphone jacks •Remote microphone connections •Remote input from PC sound card, MP3 player or iPod™ •IR repeater connection •Remote triggering of A/V components •Low voltage DC connection **•Sold individually**

Order #	MSRP	(1-3)	(4-up)
50-7753	$12.95	$7.39	$6.29



MCM CUSTOM AUDIO Keystone Mount DC Power Connection

This keystone insert features a standard barrel jack which accepts connection from most AC adaptors. It is essential when low voltage must be inserted into a Cat 5 pair for remote distribution. It is ideal for remote powering of small LCD monitors, video cameras, IR repeater systems and similar items. Rear mounted IDC connector allows simple, fast connection to unterminated 22~24AWG solid or stranded wire. Maximum voltage: 24VAC/DC, 1A. Barrel size: 2.1mm I.D., 5.5mm O.D. **•Sold individually**

Order #	MSRP	(1-3)	(4-up)
50-7752	$11.95	$6.99	$5.95

Input Source Switch Boxes

Tabletop control box allows selection of multiple input sources. Ideal when connecting several audio devices, such as CD players, VCRs, laser disk players and satellite receivers to home stereo equipment. Models available to select from three, four or five sources. Internal PC board design provides quiet, reliable operation. All connections are all RCA type female. Metal case has non-skid rubber feet and stays securely fixed in place. Dimensions: 6.9" (W) x 2.2" (H) x 3.9" (D).

Order #	Positions	(1-5)	(6-9)	(10-up)
50-6170	Three	$14.25	$13.03	$10.98
50-6175	Four	15.49	14.45	11.92
50-6180	Five	16.50	15.27	12.10

MCM CUSTOM AUDIO Six Input Line Level Stereo Source Selector

•Accommodates six sources •RCA type phono jacks •6" (W) x 2.75" (H) x 5" (D)

Order #	MSRP	(ea.)
50-5725	$99.95	$63.95

Three-Way Audio/Video Switch Box

Tabletop control box allows selection of multiple A/V sources. Ideal when connecting several devices, such as CCTV cameras, camcorders, VCRs, laser disk players and satellite receivers to a single video monitor or VCR. Accommodates video and left and right audio, all connections are all RCA type female. Metal case has non-skid rubber feet and stays securely in place. Dimensions: 6.9" (W) x 2.2" (H) x 3.9" (D). Sloped front, black color.

Order #	(1-5)	(6-9)	(10-up)
50-6195	$19.95	$18.95	$15.09

A/B Input Source Switch Box



Compact control box allows selection of two input sources into a single auxiliary or tape input. Single push button switch selects source "A" or "B". Ideal when connecting audio devices such as CD players, VCRs, laser disk players and satellite receivers to home stereo equipment. Output connection is made via attached 5' lead, terminated with male RCA type connectors, color coded red and white. Input connections are RCA type female. Rugged metal enclosure is black in color, dimensions: 3" (W) x 1" (H) x 3" (D) including switch and connections.

Order #	(1-5)	(6-9)	(10-up)
50-6220	$8.99	$8.19	$7.49

MCM 1-800-543-4330 Fax 1-800-765-6960

MCM CUSTOM AUDIO

Dual Channel Ground Loop Isolator

Ground loop problems in A/V systems normally appear as hum in speakers or horizontal bars on video monitors. These problems typically occur when multiple components receive AC power from different locations, or because CATV, satellite or antenna systems provide a separate ground point. This isolator solves that problem by providing ground path isolation between components, while maintaining full frequency response. **Features:** •Rugged steel enclosure •RCA input and output connections •Fully independent L/R channels **Specifications:** •Frequency response: 10Hz~50KHz •THD: 0.01% •Dimensions: 1.50" (H) x 3.50" (W) x 2.50" (D) •Passive device, requires no power

Order #	MSRP	(1-3)	(4-up)
50-9040	$49.95	$31.95	$26.95



Input Interface Cable for iPod™

5' cable allows connection of your iPod™ to any amplifier with standard line level inputs. It is perfect for use with home theater and distributed audio systems, as well as autosound systems having RCA line level inputs. Proprietary connector inserts directly into the bottom of the iPod™ and provides fixed line level output through L/R RCA male connectors. Cable assembly also provides regulated power supply to the iPod™ allowing it to be charged or powered from external 12VDC source.

Order #	(ea.)
50-9185	$17.95

Input Source Mixer/ Headphone Amplifier

Versatile table-top device features two stereo line level inputs and a single line level output, allowing the user to mix two sources into one. Slide controls allow independent gain adjustment for each source. Front panel 3.5mm stereo headphone jack, with slide level control, is provided for monitoring of the mixed source. Compact unit is perfect for any application requiring a low cost line mixer, or headphone amplifier. Metal case has non-skid rubber feet and stays securely in place. All connections, except headphone, are RCA type female. Requires 12VDC, 100mA. AC adaptor included. Dimensions: 1¾" (H) x 5" (W) x 4½" (D). Black color.

Order #	(1-4)	(5-9)	(10-up)
50-6182	$26.95	$24.95	$21.95

MCM CUSTOM AUDIO

Phono Input Attenuator

Device allows standard line level items to be played through magnetic phono inputs, commonly found on older home audio receivers and mixing consoles. CD/DVD/ MP3 players, tape decks, VCRs, computer sound cards and tuners may now be connected to unused phono inputs. In addition to providing the required signal attenuation, this unit provides passive equalization to compensate for the RIAA curve that is present on magnetic phono inputs. Inputs are RCA female, outputs are male RCA connections on a 7" pigtail. Passive device requires no power. Dimensions: 1" (H) x 2.25" (W) x 3" (D)

Order #	MSRP	(1–3)	(4–11)	(12-up)
50-7240	$14.59	$10.59	$9.19	$8.29

MCM CUSTOM AUDIO

24 Bit/96K D/A Convertor

This compact unit will accept standard coax or Toslink SPDIF signal, and convert it to line level audio. It is perfect when there is a need to send digital audio signal to an amplifier not having digital inputs, including home audio receivers, prosound amplifiers and mixing consoles. It is perfect when an unused digital output on a piece of home theater equipment needs to be sent to a separate whole house audio amplifier. **Features:** •Two Toslink inputs •Two coax inputs •Four-position input selector with LED indication •¼" headphone output with adjustable level •Separate REC and AMP line level L/R RCA outputs (both fixed level) •LED power indicator **Specifications:** •Digital input: 96KHz (standard SPDIF) •Resolution capability: 24 bit •Amplitude linearity: 1.06dB •Frequency response: 20Hz~20KHz •Channel separation: 100dB @ 1KHz •S/N ratio: 103dB •THD: <0.0015% •Digital filter: 82dB •Headphone output: 700mW, 8~32ohm •Power requirements: 12VDC, AC adaptor included •Dimensions: 1½" (H) x 9¾" (W) x 4½" (D)

Order #	MSRP	(1-3)	(4-up)
50-7774	$179.00	$105.00	$89.95

Stereo Phono Preamp

•30Hz~20KHz response •6mV input produces 500mV out •50Kohm impedance •SN ratio over 60dB •Uses standard 117VAC •For use with amplifers without a magnetic phono preamp

Order #	(1-9)	(10-up)
40-630	$19.95	$17.95

MCM CUSTOM AUDIO

Audio LeveliZer™ Line Level Stabilizer



Maintains a constant average output loudness, regardless of the audio source type or loudness. Perfect for louder than program commercials on radio and TV, and volume variations between different broadcasting stations, records and CDs (perfect for multi-disc players). Connect to the tape loop of any amplifier or receiver, or between the pre-amp and power amplifier, or between audio outputs of TV or VCR and amplifier inputs. Because this device monitors average input level, normal program dynamics experienced in high action video scenes are maintained. Dimensions: 2⅛" (H) x 7⅛" (W) x 3¾" (D) exluding control knob. Black in color.

Order #	MSRP	(ea.)
50-6155	$299.00	$242.00

CLEARANCE

MCM CUSTOM AUDIO

Phono Preamplifier

Allows turntable with magnetic cartridge to be played through conventional line level amplifier inputs. Use to connect a turntable to newer home theater equipment, a computer sound card, mixing console, or other professional equipment. Provides necessary RIAA equalization Four-position input selector allows one turntable and three line level devices to be selected at a single input.

Order #	MSRP	(ea.)
50-7772	$59.95	$19.00

MCM CUSTOM AUDIO

Phono Preamp with Input Selector

This pre–amplifier allows a turntable to be played through conventional line level inputs such as aux, tape, tuner or CD. It is also useful for operating a turntable with a computer sound card, mixing console, or other professional equipment. In addition to providing the required gain, it adds necessary RIAA equalization to compensate for the industry standard EQ curve utilized on LPs. Front panel phono/aux input selector allows an additional line level source to be connected. Unit features L/R RCA female type inputs and outputs, plus a separate ground lug •Power requirements: 12VDC, AC adaptor included •Dimensions: 1⅜" (H) x 5⅝" (W) x 3" (D)

Order #	MSRP	(1–3)	(4–up)
50-7770	$49.95	$31.95	$26.95

audio-technica

Phono Preamplifier

High-quality preamplifier is built to the exacting standards that made Audio-Technica one of the largest magnetic phono cartridge manufacturers in the world. It is perfect when turntables need to be played through conventional line level amplifier inputs. Use to connect a turntable to newer home theater equipment, to a computer sound card, mixing console, or other professional equipment. In addition to providing the required gain, it adds necessary RIAA equalization to compensate for the industry standard EQ curve utilized on LPs. Unit features L/R RCA female type inputs and outputs, plus a separate ground lug. **Specifications:** •Frequency response: 20Hz~20KHz •S/N ratio: 80dB •Input sensitivity: 2.5mV •Phono input impedance: 47Kohm •Power requirements: 15VDC, 20mA, AC adaptor included •Dimensions: 1.18" (H) x 2.76" (W) x 3.62" (D)

Order #	(1-3)	(4-up)
50-7778	$99.95	$89.95

ART
APPLIED RESEARCH AND TECHNOLOGY

DJPRE-II Phono Preamplifier

Since newer receivers typically do not include magnetic phono connection, this pre–amplifier is required to connect a turntable to a conventional line level input. It is also necessary if playing LPs through a computer sound card, mixing console, or other professional equipment. In addition to providing the required gain, this unit also adds necessary RIAA equalization to compensate for the industry standard EQ curve utilized on LPs. **Features:** •L/R RCA inputs and outputs •Adjustable ±10dB gain •Selectable 100pF/200pF input capacitance •Switchable 3dB low cut at 22Hz •Signal clip indicator •Turntable ground lug •Power requirements: 7~12VDC or 9~12VAC •AC adaptor included •Dimensions: 1.75" (H) x 4.2" (W) x 3.5" (D)

Order #	(ea.)
555-2716	$47.95

ART
APPLIED RESEARCH AND TECHNOLOGY

Phono Preamplifier/USB Interface

This high quality USB audio interface with standalone RIAA phono preamp acts as an interface between your computer and a wide variety of analog and digital sources. Analog inputs are switchable between phono and line level signals and a low cut filter removes rumble and wind line output jacks are always connected to the input preamps signal for source monitoring. The unit may be powered by an included AC adaptor or from USB port. Optical TOSLINK in/outs and S/PDIF input let you use this as a digital audio to USB interface as well. It will work with the USB audio device drivers built into Windows 98SE/ME/2000/XP or Macs with native USB support OS9.1 or greater or OSX. No special drivers required. **Specifications:** •Frequency response: 10Hz~50KHz •THD: .01% dB •A/D & D/A: 16 bit, 44.1KHz or 48KHz USB selectable •Dimensions: 1.75" (H) x 4.2" (W) x 3.5" (D)

Order #	(ea.)
555-2717	$104.00

audio-technica

Belt Drive Turntable with Built-In Preamp

The highly popular AT-PL50 belt drive turntable from Audio-Technica can allow you to transfer vinyl to PC for digital conversion and storage. This fully automatic turntable features an internal preamplifier which provides RIAA equalization and compatibility with standard line level inputs, and may be switched off for use with magnetic phono inputs. **Other features include:** •Soft damped cuing lever •Included cartridge and stylus •Metal platter •Included base and dustcover

Order #	(1–2)	(3–up)
555-2092	$79.95	$74.95

audio-technica

Direct Drive Turntable

Rugged turntable is ideal for DJ or home theater applications where performance and durability are a must. High torque, quartz–locked, direct–drive motor provides highly accurate speed control, with immeasurable subsonic rumble. Internal preamplifier provides RIAA EQ compensation for direct connection to line level inputs on home theater receivers, mixing consoles and computer sound cards. **Features:** •All metal "S" shaped tone arm •Included Audio-Technica cartridge, stylus and head–shell •Aluminum platter •Pitch control •Quartz lock design •Anti skate adjustment •Stylus target light •Slip mat •Forward/reverse button •33/45/78 speeds •Included output cables •Start/stop button •High-torque braking •Counterweight and height adjustment •Strobe indicators •Adjustable feet •Hinged dust cover

Order #	(1–2)	(3–up)
555-2094	$249.00	$225.00

MCM CUSTOM AUDIO

Indoor/Outdoor/Monitor Speaker Pair

Versatile speaker pair includes all of the features required to suit virtually any compact speaker application, at a tremendous price. Wide frequency response makes them suitable in main, satellite or monitor speaker situations, in the home or studio. Although outstanding when used alone, these speakers provide incredible performance when used with a subwoofer. Polypropylene cone woofer with rubber surround, and mylar dome tweeter provide outstanding frequency response, with high immunity to the elements. Internal 70V transformer allows compatibility with multi speaker commercial sound installations. Rear mounted rotary switch allows easy selection of 70V taps and 8ohm setting. Optional speaker brackets allow easy mounting to walls, ceilings and under outside overhangs. **Specifications:** •Power capacity: 30W/60W RMS/peak •Frequency response: 80Hz~20KHz •SPL: 88dB •Impedance: 8ohm •70V transformer taps: 5W, 10W, 20W, 30W, 8ohm •Dimensions: 9" (H) x 6" (W) x 5½" (D) •**Sold in pairs**

Order #	Color	MSRP	(1-3 prs.)	(4-11 prs.)
80-492	Black	$99.95	$79.95	$75.95
80-493	White	99.95	79.95	75.95

MCM CUSTOM AUDIO

Speaker Brackets

Designed specifically for use with MCM #80-492 and 80-493 speaker systems. **Sold in pairs.**

Order #	Color	MSRP	(1-3 prs.)	(4 prs.-up)
80-502	Black	$9.95	$8.50	$7.75
80-504	White	9.95	8.50	7.75



Speaker Brackets

•All steel brackets designed for wall mounting speakers •Mount speakers weighing up to 40 pounds •Fully adjustable to any position •Must be stud mounted •**Sold in pairs**

Order #	(1-4 prs.)	(5 prs.-up)
50-620	$40.95	$35.95

MCM CUSTOM AUDIO



Outdoor "Rock" Speaker System

The perfect way to easily and inconspicuously place high quality sound outdoors. Rock speakers are ideal in gardens, around decks or by the pool. Designed to blend seamlessly into any landscape, these natural looking enclosures are stone gray color, with the appearance and feel of a real landscape stone. Each rock speaker consists of an 8" polypropylene woofer, with rubber surround, and 1" mylar dome tweeter. These offer high resistance to the weather while providing full frequency response. **Specifications:** •Power capacity: 50W/100W RMS/peak •Frequency response: 20Hz~20KHz •SPL: 90dB 1W/1M •Impedance: 8ohm •Dimensions: (approximate) 15" (H) x 20" (W) x 12" (D) •Color: Stone gray •Includes 6' attached speaker cable •**Sold individually**

Order #	MSRP	(1–3)	(4–11)
50-5376	$149.95	$84.95	$79.82



breatheaudio

Resonate™ Outdoor Rock Speakers

Attractive, realistic rock finish compliments any landscape setting. Completely sealed exterior surface provides long term durability and resistance to the elements. **Features:** •6½" poly cone woofer with rubber surround •13mm diameter mylar dome tweeter •Safety loop for securing to the ground **Specifications:** •Power capacity: 70W RMS •Frequency response: 80Hz~20KHz •Sensitivity: 89dB (W/M) •Dimensions: 9½" (H) x 10½" (W) x 9½" (D) •**Sold in pairs**

Order #	Model #	Color	(pr.)
50-4662	BA-650RK-GT	Granite	$99.95
50-4663	BA-650RK-SA	Sandstone	99.95



JobSite PURE CUSTOM

Two-Way Rock Speaker

Attractive compact garden landscaping speaker is constructed from fiberglass strengthened plastic, providing high-quality sound in a natural looking stone enclosure. **Features:** •5¼" injection molded polypropylene cone woofer with butyl rubber surround •¾" liquid cooled polycarbonate dome tweeter •Multi-layer fiberglass construction •Weather and UV resistant •Rust proof aluminum grill •Attached 36" direct bury cable with waterproof wire nuts **Specifications:** •Power capacity: 10~100WRMS •Frequency response: 70Hz~21KHz •Impedance: 8ohm •Gray color •Dimensions: 9½" (H) x 10" (W) x 8½" (D) •Mfr. #LSR-5 •**Sold individually**

Order #	(ea.)
50-8550	$125.00

JobSite PURE CUSTOM

Two-Way Rock Speaker

Attractive compact garden landscaping speaker is constructed from fiberglass strengthened plastic, providing high quality sound in a natural looking stone enclosure. **Features:** •6½" mica filled polypropylene cone woofer with butyl rubber surround •1" liquid cooled soft dome tweeter •Multi-layer fiberglass construction •Weather and UV resistant •Rust proof aluminum grill •Attached 36" direct bury cable with waterproof wire nuts **Specifications:** •Power capacity: 10~150W RMS •Frequency response: 60Hz~21KHz •Impedance: 8ohm •Gray color •Dimensions: 12" (H) x 14" (W) x 11" (D) •Mfr. #LSR-6 •**Sold individually**

Order #	(ea.)
50-8551	$155.00

MCM
1-800-543-4330
Fax 1-800-765-6960

speco technologies

AWD Series In/Outdoor Speaker Pair



All weather design makes these the ideal choice for both indoor and outdoor sound installations. Larger woofer size and higher power capacity also makes these suitable in foreground music applications. Included "U" brackets and wedge design allow a wide variety of mounting capabilities. Available in 8ohm or 25V/70V transformer configurations, they are perfect for most residential or commercial sound applications. **Features:** •High immunity to outdoor elements •6½" mica cone woofer •Rubber surround •½" PEI dome tweeter **Specifications:** •Power capacity: 50W/100W RMS/peak •Frequency response: 54Hz~20KHz •SPL: 89dB (W/M) •Transformer taps 3.75W, 7.5W, 15W and 30W (70V/25V models only) •Non transformer model impedance: 8ohm •Dimensions: 10⅞" (H) x 8¾" (W) x 6¾" (D) •Available in black or white •**Sold in pairs.**

Order #	Color	Transformer	(1–3 prs.)	(4 prs. –up)
50-7550	Black	No	$148.00	$127.00
50-7551	White	No	155.00	133.00
50-7560	Black	Yes	167.00	142.00
50-7561	White	Yes	167.00	142.00

Weather Resistant Foreground/ Background Speaker Pair

This quality speaker pair is designed to provide excellent sound quality in commercial or home music installations. Wedge shape and included "U" bracket allows easy mounting on walls, from the ceiling, or in corners. Sealed reinforced polypropylene housing and high power capacity make these suitable in demanding applications, indoors or out. Aluminum grills and brackets will not rust. 5" mica cone woofer and ½" dome tweeter offer 45Hz~22KHz frequency response, 75W/150W nominal/max power capacity and 90dB sensitivity. Models with built-in 70V/25V line transformer include an external rotary selector for 5, 10, 15, 20 and 30 watt taps or 8ohm use. Great for multi-speaker commercial applications. Dimensions: 9⅞" (H) x 7⅛" (W) x 5¾" (D). **Sold in pairs.**

Order #	Color	(1-3 prs.)	(4 prs.-up)
Without Transformer			
50-5977	Black	$89.95	$84.95
50-5978	White	89.95	84.95
With Transformer			
50-5982	Black	105.00	98.95
50-5983	White	105.00	98.95

Weather Resistant Foreground/ Background Speaker Pair

This quality speaker pair is ideal for use on decks, patios, automobiles or in surround sound applications. Included "U" brackets allow easy mounting on walls or from the ceiling. Moisture and weather resistant housing, and polypropylene components allow use indoors or out. 4" long excursion woofer, 2" midrange and ¾" tweeter offer 90Hz~20KHz frequency response, 25W/40W RMS/peak power capacity and 85dB sensitivity. Dimensions: 7⅜" (H) x 4⅝" (W) x 4⅝" (D). 4~8ohm compatible. Nominal impedance 6ohm. **Sold in pairs.**

Order #	Color	(1-3 prs.)	(4 prs.-up)
50-5995	Black	$31.95	$29.95
50-5996	White	31.95	29.95

speco technologies

AWD Series In/Outdoor Speaker Pair

All weather design makes these the ideal choice for both indoor and outdoor sound installations. Included "U" brackets and wedge design allow a wide variety of mounting capabilities. Available in 8ohm or 25V/70V transformer configurations, they are perfect for most residential or commercial sound applications. **Features:** •High immunity to outdoor elements •5¼" polypropylene woofer •Rubber surround •½" PEI dome tweeter **Specifications:** •Power capacity: 40W/80W RMS/peak •Frequency response: 60Hz~20KHz •SPL: 88dB (W/M) •Transformer taps 3.75W, 7.5W, 15W and 30W (70V/25V models only) •Non transformer model impedance: 8ohm •Dimensions: 8¾" (H) x 7" (W) x 5⅜" (D) •Available in black or white •**Sold in pairs**

Order #	Color	Transformer	(1–3 prs.)	(4 prs.–up)
50-7540	Black	No	$119.00	$99.75
50-7541	White	No	125.00	105.00
50-7545	Black	Yes	142.00	121.00
50-7546	White	Yes	135.00	115.00



speco technologies

Indoor/Outdoor Speaker Pair

Compact speakers are ideal for use with a subwoofer in a compact home theater arrangement, or as satellites in remote locations including the patio, deck or near the pool. The fully weatherproof ABS housing, polypropylene cone woofer and mylar tweeter enable permanent mounting outdoors. Mounting brackets and hardware are included. **Specifications:** •Power capacity: 30W/50W RMS/peak each •Frequency response: 55Hz~20KHz •Impedance: 8ohm •Dimensions: 7¼" (H) x 4½" (W) x 4⅜" (D) •Available in black or white •**Sold in pairs**

Order #	Color	(1–3 prs.)	(4 prs.–up)
50-6580	Black	$68.95	$61.95
50-6581	White	68.95	61.95

MCM CUSTOM AUDIO

Outdoor Volume Control

Specifically designed for outdoor applications, this volume control features a specially designed gasketed PVC enclosure, and is ideally suited for use with landscaping "rock" speaker and other outdoor systems. The housing attaches to standard ¾" PVC conduit for simplified watertight installation. Internal jumpers are provided for x1, x2, x4, x8 and x16 impedance multipliers, allowing compatibility in standard and impedance matched installations. **Features** •Detachable screw terminal strips accept up to 14AWG speaker cable •12 step attenuation •May be anchored by PVC conduit alone or with the four attached wall mount tabs •Gray PVC enclosure with matching knob **Specifications** •Power capacity: 100W RMS •Frequency response: 35Hz~20KHz •Enclosure dimensions: 4¾" (H) x 3" (W) x 3¼" (D)

Order #	MSRP	(1-3)	(4-9)	(10-up)
50-7885	$74.95	$42.95	$37.95	$34.95

Indoor/ Outdoor Corner Speaker Pair



Obtain home theater quality sound in commercial environments, in or out of doors. 8ohm and 70V line compatibility allow use with residential or commercial sound systems. The high excursion woofer, coupled with a high efficiency dome tweeter provides wide frequency response with tremendous detail. Rear mounted rotary switch selects multiple taps on the 70V transformer, or 8ohm bypass position, allowing the speaker to see the full frequency range. **Features:** •Poly cone woofer with rubber surround •Transformer taps: 10W, 20W, 30W, 40W (50W on #555-2500 only) •Includes mounting brackets •Wedge shape design for improved cabinet performance and easy corner mounting •Rustproof perforated aluminum grills **Specifications #555-2500:** •Power capacity: 125W/250W RMS/max •Frequency response (8ohm mode): 50Hz~20KHz •SPL: 90dB (W/M) •Dimensions (each): 14.2" (H) x 10.6" (W) x 9.6" (D) **#555-2502:** •Power capacity: 80W/160W RMS/max •Frequency response (8ohm mode): 55Hz~20KHz •SPL: 89dB (W/M) •Dimensions (each): 13.6" (H) x 8.75" (W) x 7.6" (D) •Color: Black •**Sold in pairs**

Order #	Woofer Size	(1–3 prs.)	(4 prs.–up)
555-2500	8"	$199.00	$179.00
555-2502	6½"	169.00	149.00

MCM CUSTOM AUDIO

Indoor/Outdoor Speaker with 70V Transformer

Full range speaker is compatible with conventional 8ohm home audio, as well as commercial 70 volt distributed systems. Treated dual cone driver provides outstanding sound quality with high immunity to moisture and humidity. It is perfect in home or commercial installations, for background music, paging, and general public address applications on patios, poolside, outdoor restaurants etc. Included heavy duty mounting bracket allows easy wall, floor or ceiling mounting, and unique dispersion lens provides even 360° sound distribution. Recessed rotary switch allows easy selection of multiple transformer taps, 8ohm position fully bypasses transformer, allowing maximum frequency response in home systems. **Specifications:** •Power capacity: 20W RMS •Frequency response: 80Hz~20KHz (excluding transformer) •Transformer taps: 2.5W, 5W, 10W, 20W •SPL: 90dB 1W/1M •Driver: 6½" dual cone •Magnet size: 10 oz. •Dimensions: 8" (dia.) x 10" (H)

Order #	MSRP	(1–3)	(4–up)
50-572	$69.95	$39.95	$38.75

See Section 1 for In-Wall and Direct Bury Speaker Wire.

JobSite PURE CUSTOM Active 10" Subwoofer

This front–firing subwoofer is perfect for any home theater or music application, and has specific features added to make it very easy to integrate into a distributed audio system. **Features:** •10" polypropylene cone woofer •L/R line level inputs •Single LFE input which bypasses the subwoofers frequency adjustment, relying on the processor in the receiver •Line level and LFE feed–through outputs •Speaker level inputs, with high pass satellite speaker outputs •0°/180° phase selector •Single sensing for auto–power–on •3~30VAC/DC trigger input to allow on command from external equipment •0°/180° phase selector **Specifications:** •Output power: 90W/125W RMS/peak •Frequency response: 30~160Hz •Crossover range: 60Hz~120Hz •Dimensions: 15.25" (H) x 14.25" (W) x 17.25" (D)

Order #	Mfr. #	(ea.)
50-8480	LSS-10	$314.00

JobSite PURE CUSTOM Active 12" Subwoofer

This front–firing subwoofer is perfect for any home theater or music application, and has specific features added to make it very easy to integrate into a distributed audio system. **Features:** •12" polypropylene cone woofer •L/R line level inputs •Single LFE input which bypasses the subwoofers frequency adjustment, relying on the processor in the receiver •Line level and LFE feed–through outputs •Speaker level inputs, with high pass satellite speaker outputs •0°/180° phase selector •Single sensing for auto–power–on •3~30VAC/DC trigger input to allow on command from external equipment •0°/180° phase selector **Specifications:** •Output power: 190W/260W RMS/peak •Frequency response: 27~160Hz •Crossover range: 60Hz~120Hz •Dimensions: 19" (H) x 14.25" (W) x 19" (D)

Order #	Mfr. #	(ea.)
50-8490	LSS-12	$411.00

For the latest Product Additions
click on...
www.mcmelectronics.com

MCM CUSTOM AUDIO Center Channel Speaker System

Attractive center channel speaker features simulated black ash vinyl veneer, and a partially transparent, removable black grill. Intended to be a perfect match to model #50-9085 bookshelf speakers, this speaker will blend beautifully with any existing system. **Features:** •Dual poly cone 4" woofers, with single piece concave cone, and rubber surrounds •½" mylar dome tweeter •Rear ported enclosure **Specifications:** •Power capacity: 80W/120W RMS/peak •Frequency response: 50Hz~20KHz •Sensitivity: 88dB (W/M) •Impedance: 8ohm •Dimensions: 6" (H) x 17.75" (W) x 6.5" (D) •**Sold individually**

Order #	MSRP	(1-3)	(4-up)
50-9080	$39.95	$29.95	$26.95

MCM CUSTOM AUDIO Bookshelf Speaker Pair

Attractive speaker pair features simulated black ash vinyl veneer, and a partially transparent, removable black grill. Intended to be a perfect match to model #50-9080 center channel speaker, they are perfectly suitable as front or rear speakers in any home theater environment. **Features:** •Poly cone 4" woofer, with single piece concave cone, and rubber surround •½" mylar dome tweeter •Rear ported enclosure **Specifications:** •Power capacity: 60W/120W RMS/peak •Frequency response: 60Hz~20KHz •Sensitivity: 87dB (W/M) •Impedance: 8ohm •Dimensions: 9.5" (H) x 6" (W) x 6.5" (D) •**Sold in pairs**

Order #	MSRP	(1-3 prs.)	(4 prs.-up)
50-9085	$49.95	$31.95	$29.95

MCM CUSTOM AUDIO Active 10" Subwoofer

This down-firing active subwoofer features a highly efficient 100W amplifier, long throw 10" low frequency driver and flared front port, for excellent low frequency response. Its subdued simulated black ash finish will complement any décor. This unit is an ideal addition with any home theater speaker system that utilizes 6~8" woofers. **Features:** •Ported ¾" MDF cabinet •0°/180° phase selector •Line level inputs, with feedthrough outputs •Speaker level inputs, with high pass satellite speaker outputs •Lighted rocker power switch •Included speaker spikes **Specifications:** •Output power: 100W/150W RMS/peak •Frequency response: 30~180Hz •Variable crossover range: 20~180Hz •Power requirements: 110VAC, 60Hz •Dimensions (excluding spikes): 14" (H) x 13.75" (W) x 14.5" (D).

Order #	MSRP	(ea.)
50-7660	$199.00	$105.00

MCM CUSTOM AUDIO Center Channel Speaker System

Beautifully crafted speaker system features a high gloss piano black finish that is sure to compliment any décor. Intended to be a perfect match to Model #50-9075 bookshelf speakers, this speaker will blend beautifully with any existing system. **Features:** •Dual poly cone 5¼" woofers, with butyl rubber surrounds •1" soft dome tweeter •Rear ported enclosure **Specifications:** •Power capacity: 125W/275W RMS/peak •Frequency response: 70Hz~20KHz •Sensitivity: 87dB (W/M) •Impedance: 8ohm •Dimensions: 6.3" (H) x 16.5" (W) x 7.9" (D) •**Sold individually**

Order #	MSRP	(1-3)	(4-up)
50-9070	$199.00	$84.95	$77.95

MCM CUSTOM AUDIO Bookshelf Speaker Pair

Beautifully crafted speaker pair features a high gloss piano black finish that is sure to compliment any décor. Intended to be a perfect match to model #50-9070 center channel speaker, they are perfectly suitable as front or rear speakers in any home theater environment. **Features:** •5¼" poly cone woofer, with rubber surround and steel phase plug •1" soft dome tweeter •Rear ported enclosure **Specifications:** •Power capacity: 75W/225W RMS/peak •Frequency response: 49Hz~20KHz •Sensitivity: 88dB (W/M) •Impedance: 8ohm •Dimensions: 9.9" (H) x 6.3" (W) x 7.9" (D) •**Sold in pairs**

Order #	MSRP	(1-3 prs.)	(4 prs.-up)
50-9075	$249.00	$99.95	$91.95

MCM CUSTOM AUDIO Dipolar Rear Channel Speaker

Dual woofers and dual tweeters, arranged in a di-polar configuration, make this speaker perfect for surround channel applications. Positioned at the rear, directly at the left and right of the listening position, these speakers provide the outstanding imaging intended for 5.1, THX and Dolby Digital systems. They are also great for compact systems in conventional two channel stereo environments. **Features:** •Dual 5¼" woofers •Dual ½" mylar dome tweeters with specially designed dispersion lens •Dual front ports •Attractive simulated black ash vinyl veneer enclosure with removable black grills •Wall mount hanger •Color coded push terminals which accept up to 16AWG wire **Specifications:** •Power capacity: 50W/100W RMS/peak •Frequency response: 80Hz~20KHz •Impedance: 8ohm •Dimensions: 11" (H) x 11" (W) x 6⅜" (D) •**Sold individually**

Order #	MSRP	(1-3)	(4-up)
50-6855	$69.95	$32.95	$29.95

MCM 1-800-543-4330 Fax 1-800-765-6960

MCM CUSTOM AUDIO

Two-Way Monitor Speaker System

This versatile two-way speaker is perfect for use as mains in small venues, stage or studio monitors, or in distributed audio environments where sound quality is a must. Housed in a heavy-duty ported ABS enclosure, the speaker system features a soft dome tweeter, and high excursion 8" woofer, and is capable of delivering 30Hz~20KHz frequency response. Internal 70V transformer allows compatibility with distributed commercial systems, and 8ohm bypass position provides full frequency response with conventional amplifiers.
Specifications: •Power capacity: 75W/150W RMS/peak •Nominal impedance: 8ohm •SPL 92dB (W/M) •Transformer taps: 5W, 10W, 15W, 20W and 30W •Dimensions: 15¾" (H) x 10" (W) x 9" (D) •Black color •**Sold individually**

Order #	MSRP	(1-3)	(4-up)
555-1864	$199.00	$125.00	$110.00

OMNI MOUNT

Universal Speaker Mounting Kit

For speakers having footing at the back of the enclosure, the WA is the best mounting solution for the widest coverage. •30 lb. weight capacity •Weatherproof •One mount per kit •Perfect for mounting MCM Custom Audio #555-1864 monitor speaker

Order #	(kit)
555-1862	$79.95

OMNI MOUNT

Audio Basics Ceiling/ Wall Speaker Mounts

The perfect value oriented companion to home theater and audio applications for mounting front, center, or rear channel speakers to either wall or ceiling. The AB2 is for larger satellite and small bookshelf speakers, weighing up to eight lbs. Each is made of durable, weather resistant fiber reinforced polymer, and includes all mounting hardware and correct drill bit, for perfect installation every time. Each model is available in black or white, and is sold individually. Specially priced five–packs are available or traditional 5.1 audio systems.

Order #	Model	Set	Color	(ea.)
50-7450	AB2	Single	Black	$17.99
50-7451	AB2	Single	White	17.99
50-7455	AB2-HTS	Five pack	Black	79.95

OMNI MOUNT

Stainless Steel Series Speaker Mounts

Designed for heavier systems, these mounts are perfect for everything from surround and satellite speakers, foreground speakers and studio monitors. Unique ball and clamp design allows wide range of movement, with secure positioning of heavy speakers. Stainless steel hardware ensures strength, durability and all weather use. Available in wall or ceiling mount versions, with weight capacity from 5 lbs. to 20 lbs., a model is available to suit any need. 5 lb. versions include hardware for wall or ceiling mount, all others must be specified. Available in black, white or gray, mounts are sold individually and include all mounting hardware and correct drill bit, for perfect installation every time. **Sold individually.**

Order #	Weight Capacity (lbs.)	Type	Color	(ea.)
50-7410	5.0	Wall/Ceiling	Black	$18.95
50-7411	5.0	Wall/Ceiling	Gray	18.95
50-7412	5.0	Wall/Ceiling	White	18.95
50-7415	10.0	Wall	Black	22.99
50-7420	10.0	Ceiling	Black	22.99
50-7425	20.0	Wall	Black	30.99
50-7426	20.0	Wall	White	30.99
50-7430	20.0	Ceiling	Black	30.99
50-7431	20.0	Ceiling	White	30.99

NEW

SONY Bravia™ 3LCD 1080i Home Theater Front Projector

✔*6,000:1 contrast ratio (with advanced iris)*

The VPLAW10 HD projector makes images look more lifelike than ever. With a screen size potential of 200" (measured diagonally), it delivers a truly cinematic experience. Sit back and enjoy the bright scenes that the advanced iris funtion delivers, while also displaying deep blacks for the perfect amount of contrast. **Features:** •720p maximum resolution •3LCD chip •165W ultra high pressure lamp **Inputs:** •Component video (Y/Pb/Pr), composite video, HDMI™, HD-15, RS-232C, S-video

Order #	(1-9)	(10-up)
VPLAW10	$1199.00	$1045.00

NEW

SONY Bravia™ 3LCD 1080i Home Theater Front Projector

✔*12,000:1 contrast ratio (with advanced iris)*

The VPLAW15 HD projector makes images look more lifelike than ever. With a screen size potential of 200" (measured diagonally), it delivers a truly cinematic experience. Sit back and enjoy the bright scenes that the advanced iris funtion delivers, while also displaying deep blacks for the perfect amount of contrast. **Features:** •720p maximum resolution •3LCD chip •165W ultra high pressure lamp **Inputs:** •Component video (Y/Pb/Pr), composite video, HDMI™, HD-15, RS-232C, S-video

Order #	(1-9)	(10-up)
VPLAW15	$1399.00	$1325.00

NEW

SONY Bravia™ SRXD™ 1080p Home Theater Front Projector

✔*15,000:1 contrast ratio (with advanced iris)*

Enjoy full 1080p high definition with three SXRD™ micro-display panels for the ultimate home theater experience. What makes the VPLVW40 so special? For starters, nothing recreates the atmosphere of going to the movies like a projector. Enjoy images up to 300" (measured diagonally). **Features:** •1080p maximum resolution •SRXD chip •3LCD chip •12 bit panel drive full digital chassis •200W ultra high pressure lamp **Inputs:** •Component video (Y/Pb/Pr), two composite video, two HDMI™, HD-15, RS-232C, S-video, 12V trigger

Order #	(1-9)	(10-up)
VPLVW40	$3499.00	$3255.00

SONY Bravia™ SRXD™ 1080p Home Theater Front Projector

✔*35,000:1 contrast ratio (with advanced iris)*

Enjoy full 1080p high definition with three SXRD™ micro-display panels for the ultimate home theater experience. What makes the VPLVW60 so special? For starters, nothing recreates the atmosphere of going to the movies like a projector. Enjoy images up to 300" (measured diagonally). **Features:** •1080p maximum resolution •SRXD chip •3LCD chip •12 bit panel drive full digital chassis •200W ultra high pressure lamp **Inputs:** •Component video (Y/Pb/Pr), two composite video, two HDMI™, HD-15, RS-232C, S-video, 12V trigger

Order #	(1-9)	(10-up)
VPLVW60	$5299.00	$5155.00

NEW

SONY 7.1 Channel Home Theater A/V Receiver

Get amazing 1080p video and 7.1 channels of pristine surround sound. This versatile audio/video receiver features HDMI™ 1080/24p capability to help you get the most from Blu-ray Disc™ movies. Also enjoy built-in XM and PMP connections

Features: •HDMI™ 1080/24p •A/V sync •Digital Cinema Sound™ •Digital media port •Dolby® Digital Decoding, Dolby® Pro Logic® II Decoding, Dolby® Digital EX Decoding, Dolby® Pro Logic® IIX Decoding, dts® 96/24 Decoding, dts® NEO:6 Decoding, dts®-ES Decoding and Dolby® Pro Logic® decoding •XM connect and play ready

Inputs: •Four composite video inputs, two optical audio inputs, coaxial audio inputs, eight RCA audio inputs, three component video input and four 1080p HDMI™ inputs

Outputs: •Three composite video output, component video output and 1080p HDMI™ connection, subwoofer output, antenna terminal (AM loop), antenna terminal (FM 75ohm), headphone output

Speaker terminal type: •Screw binding posts (A & B)

Order #	(1-9)	(10-up)
STR-DG920	$659.00	$634.00

SONY Home Theater A/V Receiver



Get amazing 1080p video and 5.1 channels of pristine surround sound. This versatile audio/video receiver features HDMI™ "Pass-through" and 1080/24p capability to help you get the most from Blu-ray Disc™ movies. **Features:** •HDMI™ Pass-through •A/V sync •Digital Cinema Sound™ •165W ultra high pressure lamp •Dolby® Digital Decoding, Dolby® Pro Logic® II Decoding, Dolby® Digital EX Decoding, Dolby® Pro Logic® IIX Decoding and Dolby® Pro Logic® Decoding **Inputs:** •Two composite video inputs, two optical audio inputs, coaxial audio input, four RCA audio inputs, two component video input and two 1080p HDMI™ inputs **Outputs:** •Composite video output, subwoofer output, antenna terminal (AM loop), antenna terminal (FM 75ohm), headphone output, component video output and 1080p HDMI™ connection **Speaker terminal type:** •Front: Banana, rear and center: Push

Order #	(1-9)	(10-up)
STR-DG520	$259.00	$234.00

SONY 7.1 Channel Home Theater A/V Receiver

✔ *3 HDMI inputs*
✔ *XM ready*

Get amazing 1080p video and 7.1 channels of pristine surround sound. This versatile audio/video receiver features HDMI™ 1080/24p capability to help you get the most from Blu-ray Disc™ movies. Also enjoy built-in XM and PMP connections.

Features: •HDMI™ 1080/24p •A/V sync •Digital Cinema Sound™ •Digital media port •Dolby® Digital Decoding, Dolby® Pro Logic® II Decoding, Dolby® Digital EX Decoding, Dolby® Pro Logic® IIX Decoding, dts® 96/24 Decoding, dts® NEO:6 Decoding, dts®-ES Decoding and Dolby® Pro Logic® decoding •XM connect and play ready

Inputs: •Four composite video inputs, two optical audio inputs, coaxial audio inputs, seven RCA audio inputs, three component video input and three 1080p HDMI™ inputs

Outputs: •Composite video output, component video output and 1080p HDMI™ connection, subwoofer output, oantenna terminal (AM loop), antenna terminal (FM 75ohm), headphone output

Speaker terminal type: •Spring clips (A & B)

Order #	(1-9)	(10-up)
STR-DG720	$359.00	$334.00

SONY S7.1 Channel Home Theater A/V Receiver

✔ *4 HDMI inputs*
✔ *XM ready*

Get amazing 1080p video and 7.1 channels of pristine surround sound. This versatile audio/video receiver features HDMI™ 1080/24p capability to help you get the most from Blu-ray Disc™ movies. Also enjoy built-in XM and PMP connections

Features: •HDMI™ 1080/24p •A/V sync •Digital Cinema Sound™ •Digital media port •Dolby® Digital Decoding, Dolby® Pro Logic® II Decoding, Dolby® Digital EX Decoding, Dolby® Pro Logic® IIX Decoding, dts® 96/24 Decoding, dts® NEO:6 Decoding, dts®-ES Decoding and Dolby® Pro Logic® decoding •XM connect and play ready

Inputs: •Four composite video inputs, two optical audio inputs, coaxial audio input, seven RCA audio inputs, three component video input and four 1080p HDMI™ inputs

Outputs: •Composite video output, component video output and 1080p HDMI™ connection, subwoofer output, oantenna terminal (AM loop), antenna terminal (FM 75ohm), headphone output

Speaker terminal type: •Screw binding posts (A); spring lever (B)

Order #	(1-9)	(10-up)
STR-DG820	$459.00	$434.00



SONY A/V Receiver

Treat your music right with 100W per channel for smooth, low-distortion sound. **Features:** •100W x 2 (8ohm, 40Hz~20KHz, THD 0.09%) •Frequency synthesis AM/FM tuning with 30 presets •Five function input selector •A or B switch/A and B switch •Analog amplifier **Includes:** •Instruction manual, FM wire antenna, remote control, AM loop antenna, two "AA" batteries •Dimensions: 16.93" x 5.22" x 11.89" •Input sensitivity/impedance: Line inputs 250mV/50Kohm •Frequency response: 20Hz~50KHz, +0/-0.5dB (with bass boost bypassed)

Order #	(1-9)	(10-up)
STR-DE197	$177.00	$167.00

SONY DVD/VCR Progressive Scan Combo Player

Watch a DVD while recording a TV show with this space-saving component. **DVD features:** •Progressive scan/output (480P) •Component output •Coaxial digital output •Fast/slow playback with sound •Disc capacity: One. **VCR features:** •4-head hi-fi stereo •Line input recording (no tuner) •Timer recording for 8 programs/month •19 micron heads for optimized EP training •SQPB (S-VHS quasi playback) •Auto head cleaner. **DVD playback format:** •DVD-RW (video/VR mode with CPRM)/ -R/+RW/+R/+R DL •MP3 (CD-R/RW, DVD-R/ -RW/+R/+RW) •Jpeg (CD-R/RW, DVD+RW/+R-R/-RW, Kodak) •Includes remote control and user's manual.

Order #	(ea.)
SLV-D380P	$121.00

SONY Five Disc DVD Changer with HDMI™ and 1080p Upscaling

The DVP-NC800H is the five disc DVD/CD player solution your home theater has been waiting for. Enjoy your DVD collection, upscaled to gorgeous 1080p via the HDMI™ connection. Plus, with BRAVIA® Sync, you can easily power on and synch the inputs of compatible Sony AV devices connected to the players via HDMI for hassle-free enjoyment. Includes AV cable and remote control with batteries. **Features:** •High resolution jpeg output •Precision cinema progressive™ technology •12 bit/108MHz video DAC •Multi disc resume •Multi brand TV remote control

Order #	Color	(1-9)	(10-up)
DVP-NC800H/B	Black	$149.00	$135.00
DVP-NC800H/S	Silver	149.00	135.00

MCM 1-800-543-4330 Fax 1-800-765-6960

AudioSource® Stereo Pre-Amplifier

This elegantly simple pre-amp offers audiophile performance, without the extravagant price. Perfectly matched in appearance and performance to the AudioSource AMP Two and AMP Three, this control unit is compatible with any amplifier accepting line level inputs. This unit provides selection of inputs labeled DVD, CD, LD, Tuner, Tape and Aux. (magnetic phono requires optional pre-amp, such as MCM #40-630). Additionally, there are two sets of line outputs and one tape loop. Rotary controls independently adjust volume, balance, bass and treble.

Order #	(ea.)
50-6065	$179.00

SONY DVD Recorder with HDMI™ and 1080p Upscaling

Archive all your favorites to DVD with the RDR-GX360 DVD recorder. Record your favorite TV shows to DVD, and quickly burn photos and personal video directly from your compatible Sony digital cameras and camcorders with "One Touch Dubbing" through the USB or i.LINK interface. There's also handy line input recording (non-tuner) and beautiful 1080p upscaling through HDMI™ from DVD. Includes AV cable and remote control with batteries. Unit is black. **Features:** •JPEG and MP3 playback •Cable box/satellite receiver control through IR blaster •BRAVIA™ Sync •Multi brand TV remote control

Order #	(1-9)	(10-up)
RDR-GX360	$199.00	$192.00

SONY DVD Recorder/VCR Combo with HDMI™ and 1080p Upscaling

The RDR-VX560 DVD Recorder/VCR combo is just what your cable box ordered. Save your favorite TV shows, archive old VHS tapes, even burn photos and personal video from Sony USB-based camcorders and digital cameras with ease. You'll also appreciate its convenient ability to bring DVD-recording into your living room. Includes AV cable and remote control with batteries. Unit is black. **Features:** •JPEG and MP3 playback •Cable box/satellite receiver control through IR blaster •BRAVIA™ Sync •Two-way "One Touch Dubbing" from VCR to DVD or reverse •Multi brand TV remote control

Order #	(1-9)	(10-up)
RDR-VX560	$249.00	$247.00

Sherwood® Dolby® Digital 7.1 Receiver

This Dolby Digital receiver provides 100W per channel for each of seven channels. **Features:** •HDMI switching •Universal Video™ up-conversion to component video •XM "Connect and Play" compatibility •Automatic speaker set-up and room EQ •Dolby Digital EX, Pro Logic IIx •DTS-ES, 96/24, Neo-6 Dolby virtual speaker •Dolby headphone •Totally discrete amplifier stage for all channels •Four DSP surround modes (theater, hall, church, matrix) •192KHz/24 bit digital to analog devices for all channels •7.1 channel direct input •Automatic speaker set-up with supplied microphone •Room EQ •Three A/V inputs •Two A/V outputs •Universal Video™ •Two component video inputs •Component video output •HDMI inputs •One HDMI output •Three analog inputs (including tuner) •Analog output •Three composite video inputs and two composite video outputs •Four digital inputs (two coaxial and two optical) •Optical digital output •Advanced multi-brand remote control •Multi-stage dynamic range control •Cinema EQ •Tone direct speaker •30 AM/FM tuner presets •30 XM tuner presets •Mfr. #RD-7502

Order #	(ea.)
50-7802	$314.00

Sherwood® Five Disc Carousel CD Changer

Front loading multi–disc player features a one–bit twin D/A convertor, random sequential play, and bright fluorescent display with music calendar. **Other features include:** •Coaxial digital output •8x oversampling •Three beam laser pick-up •Headphone output with volume control •Compatibility with Sherwood Digi–Link remote control system •Mfr. #CDC-5090R

Order #	(ea.)
50-6321	$194.00

PYRAMID® AM/FM Digital Tuner

The ideal mate for the PR330A Stereo Amplifier, this quartz locked tuner is compatible with any amplifier with line level inputs. The IR remote control included with the PR330A will operate this tuner. **Features include:** •Bright fluorescent digital display •20 station memory •Auto station scanning •Signal lock indicator RCA pre-amp out •Included AM and FM antennas •Dimensions: 16" (W) x 4" (H) x 9" (D) •Black color •Mfr. #PR33T

Order #	(ea.)	(2-up)
50-6045	$79.95	$70.95

Sherwood® Dolby Digital/ DTS Receiver

Built on the same chassis as its upscale sibling the RD-8601 (#50-7785), the RD-6500 is the perfect foundation for a budget priced 5.1 system. This unit includes built-in decoders for DTS, Dolby Digital and Dolby Pro Logic II. **Features:** •100W per channel x 2 in stereo mode with less than 0.9% THD, 40Hz~20KHz @ 6ohm •100W x 5 in surround mode •Two coaxial and one optical digital input •Subwoofer preamp output •Three A/V inputs •Four audio inputs •6 channel direct input •Front panel A/V input •Dynamic range control •30 station presets •See www.mcmelectronics.com for complete information

Order #	Model #	(ea.)
50-7800	RD-6500	$177.00

Sherwood® Stereo Receiver

Straight-forward AM/FM receiver features outstanding tuner sensitivity, multiple component inputs, and a solid, discrete output, 100W RMS x two channel stereo amplifier. Additionally, the included remote control operates the relay switching for the A/B speaker outputs. **Features:** •AM/FM stereo tuning with 30 station presets •Large fluorescent display •Included 25 key IR remote control •Four line level inputs (plus tuner) •Digital encoder volume control •Headphone jack •Sleep timer **Specifications:** •THD: <0.08%, 20Hz~20KHz @ 8ohm •S/N ratio: >90dB •IHF FM tuner sensitivity: 17.2dBf •FM frequency response: 40Hz~12KHz •AM tuner sensitivity: 800µV/M •AM frequency response: 100Hz~2.3KHz • Dimensions: 4⅛" (H) x 17⅜" (W) x 14" (D)

Order #	Mfr. #	(ea.)
50-7805	RX-4105	$131.00

Sherwood® Stereo Receiver

Straight-forward AM/FM receiver features outstanding tuner sensitivity, multiple component inputs, and a solid, discrete output, 100W RMS x two channel stereo amplifier. **Features:** •AM/FM stereo tuning with 30 station presets •Large fluorescent display •Included IR remote control •Four line level inputs (plus tuner) •Digital encoder volume control •Headphone jack •Sleep timer •Mfr. #RD-4109

Order #	(ea.)
50-7806	$114.00

AudioSource® EQ 200 Stereo Graphic Equalizer

Provides equalization of the entire spectrum, with ten bands per channel, one octave apart. Left and right input level controls allow perfect matching. Multi colored spectrum display shows relative level of each band. Each of the 20 slide controls allows easy visual identification of settings. Rear panel has connections for audio and video inputs and outputs, two sets of tape inputs and outputs. Front panel controls include EQ bypass switch, EQ record and tape monitor selection.

Order #	(ea.)
50-6090	$131.00

KINYO 5.1 Digital Sound Bar

The Kinyo ArtDio® amplified sound bar with matching subwoofer delivers 5.1 audio with surprising performance and surround effect. The sound bar measures 31½" wide, and houses five 3" full range drivers, each driven by independent amplifier channels. The drivers are specifically positioned within the enclosure to provide three-dimensional realism amazingly similar to speakers surrounding the listener. A separate active subwoofer features an 8" driver in a tuned ported enclosure, and is powered by its own 60W amplifier. The internal decoder supports Dolby® Digital, DTS®, Dolby® Pro-Logic® II and accepts both Toslink and coaxial digital inputs. It is a perfect match for flat panel monitors in areas where an overly involved home theater system is not desired or practical. **Features:** •Two optical and two coaxial inputs •Two analog L/R stereo inputs •Discrete six channel 5.1 input •Included 21 button IR remote control •Backlit LCD display showing settings, functions and operation •Includes connecting cables required for most applications, and wall mount hardware **Specifications: sound bar:** •Power output: 12W five channels •Dimensions: 5.51" (H) x 31.5" (W) x 5.12" (D) **Subwoofer:** •Power output: 60W •Dimensions: 15.35" (H) x 7.48" (W) x 13.39" (D) •Power requirements: 120VAC, 60Hz, 240W. •Mfr. #HT-1037 •**Suggested list $349.95**

Order #	(ea.)
50-9300	$299.00

Sherwood® Three Input HDMI Link™ Switcher

This table top switcher accepts component video, and two HDMI inputs, and provides a single HDMI output. Each input includes a Toslink connection, so the digital audio is added to the HDMI data stream. A separate Toslink output is also provided for connection to an A/V receiver. Input selection can be made from a front panel selector, an included IR remote control, or by external RS-232 control. **Features:** •Low profile black housing •Brushed aluminum front panel •Blue LED indicators for input and power •3.5mm input for connection of an external IR sensor •Full HDCP compliance •Dimensions: 2⅜" (H) x 17⅜" (W) x 9⅜" (D) •Includes 6' HDMI cable •Mfr. #HSB-6501

Order #	(ea.)
50-7813	$229.00

MCM CUSTOM AUDIO Two-Way Monitor Speaker System

This versatile two-way speaker is perfect for use as mains in small venues, stage or studio monitors, or in distributed audio environments where sound quality is a must. Housed in a heavy-duty ported ABS enclosure, the speaker system features a soft dome tweeter, and high excursion 8" woofer, and is capable of delivering 30Hz~20KHz frequency response. Internal 70V transformer allows compatibility with distributed commercial systems, and 8ohm bypass position provides full frequency response with conventional amplifiers. **Specifications:** •Power capacity: 75W/150W RMS/peak •Nominal impedance: 8ohm •SPL 92dB (W/M) •Transformer taps: 5W, 10W, 15W, 20W and 30W •Dimensions: 15¾" (H) x 10" (W) x 9" (D) •Black color •**Sold individually**

Order #	MSRP	(1-3)	(4-up)
555-1864	$199.00	$125.00	$110.00

PYRAMID® Professional Home/Studio Stereo Preamplifier

May be used on a tabletop or mounted in a rack, making it suitable for professional or high end home use. Front panel includes an input for microphone, with level control. Rotary controls adjust volume, loudness, bass, treble and midrange. Other features include hi/low filter, stereo/mono mode selector. Push buttons select from up to five inputs labeled Tape, Tuner, CD, Aux and Phono. All inputs accept standard line level, except phono input which accepts low level for magnetic cartridge. **Specifications:** •Input sensitivity: •Mic: 0.5mV/600ohm •Phono: 3mV/47Kohm •Others 150mV/47Kohm •Output level: •Tape out: 150mV/100Kohm •Pre out: 500mV/4Kohm •THD: <0.4% •Frequency response: 5Hz~30KHz •Connections: Mic input: ¼", all others RCA type female •Power requirement: 120/220VAC 50~60Hz •Dimensions 19" (W) x 2⅜" (H) x 8½" (D) •Mfr. #PR-2500

Order #	(ea.)	(2-up)
555-4051	$79.95	$73.95

PYRAMID® Professional Home/Studio Stereo Crossover

Professional three way, six channel crossover is suitable for club or high end home use. Ideal for any multi-amp application. **Provides the following adjustments: Low** •Low pass cuttoff of 50Hz, 90Hz, 180Hz, 360Hz, 720Hz; **Mid** •High pass cutoff of 50Hz, 90Hz, 180Hz, 360Hz, 720Hz •Low pass cutoff of 1KHz, 2KHz, 4KHz, 6KHz, 8KHz; **High** •High pass cutoff of 1KHz, 2KHz, 4KHz, 6KHz, 8KHz. **Features include:** •Individual level control for low, mid and high frequency channels •Rack mount chassis with handles •RCA input and output connections •Switchable 110/220V operation **Specifications:** •Filter slope 12dB/octave •Frequency response •20Hz~20KHz •S/N ratio 90dB •THD ±0.01% •Dimensions 19" (W) x 2⅜" (H) x 8½" (D) •Mfr. #SEA-3000

Order #	(ea.)	(2-up)
555-4050	$69.95	$64.84

PYRAMID® Home/Studio Stereo Equalizer

Rack mount EQ provides individual left/right control of 15 frequency bands from 25Hz to 16KHz. Three position selector allows slide controls to operate across (6dB, 9dB or 12dB boost/cut range. Five segment (per channel) bargraph display shows relative input to output signal level. **Provides control of the following frequencies:** 25Hz, 40Hz, 63Hz, 100Hz, 150Hz, 250Hz, 630Hz, 1KHz, 1.5KHz, 2.5KHz, 4KHz, 6.3KHz, 10KHz and 16KHz. **Features include:** •Individual left/right bypass switch •Rack mount chassis with handles •RCA input and output connections •Switchable 110/220V operation **Specifications:** •Frequency response •5Hz~20KHz •S/N ratio 90dB •THD <0.02% •Dimensions 19" (W) x 1¾" (H) x 9⅝" (D) •Mfr. #PEQ-60

Order #	(ea.)	(2-up)
555-4045	$89.95	$83.95

Front

Back

Sherwood® Distributed Audio Stereo Receiver

This receiver is perfect for music listening in any room of the home, with conventional left/right stereo output. What sets this apart is four amplifier output channels, creating a self contained, four-zone distributed audio receiver. Up to four pairs of bookshelf, in-wall, in-ceiling or outdoor speakers may be driven directly from this unit, with independent selection of any or all pairs. It is perfect in small residential or commercial background music applications. **Features:** •AM/FM tuner with 30 station presets •Five audio inputs (including tuner) •Phono input •IR remote control •Volume, bass and treble controls •Headphone jack •Power output: 70W RMS x 4 (8ohm), 100W RMS x 4 (4ohm) •THD: <0.2%, 20Hz~20KHz into 8ohm •Dimensions: 5" (H) x 17⅜" (W) x 13" (D) •Mfr. #RX-5502

Order #	(ea.)
50-4640	$209.00

PYLE PRO Dual Cassette Deck

Dual cassette deck is the perfect addition to any home theater system requiring tape capability. Included mounting hardware also allows the unit to be easily installed in a standard 19" equipment rack. **Features:** •Dynamic noise reduction •Normal and high speed dubbing •CrO^2 and normal tape selector •Three digit tape counter •LED level meters • Capability for use with IR remote when used with the matching PT600A integrated amplifier •110/220V switchable power input •Dimensions (excluding rack ears): 5.5" (H) x 16.5" (W) x 9" (D) •Mfr. #PT649D

Order #	(1-3)	(4-up)
50-6650	$93.95	$92.95

#24-6595

MCM Rear Panel A/V Extenders

Easily connect and re-connect video games, camcorders and portable audio/video devices to your television's audio/video inputs without having to turn the television around each time. These extenders will save your back from strains and virtually eliminate the danger of dropping your television every time you plug into the A/V inputs. Standard A/V inputs via "RCA" type jacks on the front or side of your television and "RCA" type plugs for the rear. Available with S-video capability for such equipped devices.

Order #	Description	(ea.)	(2-4)	(5-up)
24-6595	A/V and S-video (shown)	$14.95	$13.50	$12.00
24-6600	A/V only	12.95	11.50	10.75

MCM
1-800-543-4330
Fax 1-800-765-6960